Product data sheet
Characteristics

9422RT1
Disconnect mechanism, circuit breaker, variable depth, 1000A, operator only, for MAL, MHL, MEL, MXL breakers



Main

Range	9422R
Product	Circuit Breaker Mechanism
Mounting Type	Flange rod variable depth
Certifications	CSA UL Recognized
Circuit Breaker Type	MAL/MHL/MEL/MXL 2 MAL/MHL/MEL/MXL 3
Handle Type	Ordered separately

Ordering and shipping details

Category	21732-9422
Discount Schedule	CP1
GTIN	785901111160
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.90 in (20.066 cm)
Package 1 Width	14.30 in (36.322 cm)
Package 1 Length	15.60 in (39.624 cm)
Package 1 Weight	14.00 lb(US) (6.35 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.