Product data sheet
Characteristics

34T145HDIT
TRANSFORMER DRY 3PH 34KVA 460V-460Y/265V

Main

Product	Drive Isolation Transformer
Enclosure Code	18D
Enclosure Type	NEMA 2
Insulation Temperature	428.0000000000 °F (220 °C)
Phase	3 phase
Primary Voltage	460 V delta
Power Rating	34 kVA
Secondary Voltage	460Y/265 V
Full Capacity Taps	2 5 % 1+ 1-
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	US10PE216266
Discount Schedule	0PE2
GTIN	785901784999
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	315.00 lb(US) (142.882 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.