

Product data sheet

Specifications



End tap box, I-Line Busway,
3000A, 600VAC, 3 phase, 4 wire,
integral ground bus, Cu, feeder,
10ft, bolted [TAA]

CF2530GETBMB

Product availability: Non-Stock - Not normally stocked in
distribution facility

Main

Product	End tap box
Range	I-Line

Complementary

Rated Current	3000 A copper
Rated Operational Voltage	600 V AC/DC 50/60 Hz
Length	39.38 in (1000.25 mm)
Height	28 in (711.2 mm)
Width	20.88 in (530.35 mm)
Material	Copper: busbar
I-LINE Value End	Bolt
Number of Phases	3 phase
For Use with	Busbar trunking 3000 A copper
Protection Type	50 percent capacity integral ground bus
Wiring Configuration	4-wire

Environment

Standards	UL 857 CSA C22.2 No 27:1994 IEC 61439-6
-----------	---

Ordering and shipping details

Category	US10PE820043
Discount Schedule	0PE8
GTIN	785901120506
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	39.4 in (100.0 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package 1 Width	20.9 in (53.0 cm)
Package 1 Length	28.0 in (71.1 cm)
Package weight(Lbs)	260.0002 lb(US) (117.934 kg)

Compliance

Compliance	TAA Compliant BAA Compliant via COTS
------------	---

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 975 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	237 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	86 kg CO2 eq.
Carbon footprint of the installation phase [A5]	7 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 561 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	84 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	94
Circularity Profile	No need of specific recycling operations
Take-back	No