# Product data sheet

Specifications



To be discontinued

## Timing Relay, Type A, pneumatic, off delay, 0.1 to 60 seconds, 15A, 600 V, timed and instantaneous, 120 VAC 60 Hz coil

9050AO11DV02

Discontinued on: Mar 31, 2026

To be end-of-service on: Jun 30, 2026

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Product Range** | 9050A/H |
| **Product Type** | Timer |
| **Timing Mode** | Off-delay |
| **Timing Range** | 0.1 s...1 min |
| **Switch Function** | SPDT |
| **Coil Voltage** | 120 V AC 60 Hz<br>110 V AC 50 Hz |
| **Contact Operation** | Time delayed 1 NO + 1 NC<br>Instantaneous 1 NO + 1 NC |
| **current rating** | 15 A |

## Complementary

| | |
|---|---|
| **maximum switching voltage** | 600 V AC |
| **electrical connection** | Screw-clamp terminals |
| **reset response time** | 29 ms - on-delay<br>27 ms - off-delay |
| **Mounting Support** | Panel |

## Environment

| | |
|---|---|
| **Ambient Temperature Range - Operational** | 68…104 °F (20…40 °C) |
| **Certifications** | UL Listed<br>CSA |
| **Height** | 2.6 in (67 mm) |
| **Width** | 4.02 in (102 mm) |
| **Depth** | 4.4 in (111 mm) |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CP121631 |
| **Discount Schedule** | 0CP1 |
| **GTIN** | 785901485919 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Returnability** | No |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 4.800 in (12.192 cm) |
| **Package 1 Width** | 3.50 in (8.89 cm) |
| **Package 1 Length** | 6.800 in (17.272 cm) |
| **Package weight(Lbs)** | 30.879 oz (875.433 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant By Exemption |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |