Product data sheet

Specifications



Main lugs unit, EZ Meter-Pak, 1200A, 240VAC max, 3ph/4W, 1200A bus, UG, Type 3R, EUSERC

EZM31200TBU

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	EZ meter-pak
Product or Component Type	Meter center main unit
Main type	Main Lugs
Included Items	Closing plate

Complementary

Main rated current	1200 A
Bus rated current	1200 A
Enclosure Material	Painted steel
[Ue] rated operational voltage	208Y/120 V AC 240/120 V delta AC
Device mounting	Surface
Number of Phases	3 phase in 3 phase out
Service feed location	UG
Electrical connection	Lugs 1 AWG 6...300 kcmil aluminium/copper) ground Studs 3line Studs 3neutral
Wiring configuration	4-wire
Height	44.71 in (1135.63 mm)
Width	33.16 in (842.26 mm)
Depth	11.68 in (296.67 mm)

Environment

Product Certifications	UL Listed EUSERC
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	US10DE400020
Discount Schedule	0DE4
GTIN	785901189428
Returnability	Yes
Country of origin	MX

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.000 in (33.020 cm)
Package 1 Width	36.600 in (92.964 cm)
Package 1 Length	46.000 in (116.840 cm)
Package weight(Lbs)	82.001 lb(US) (37.195 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	2
Package 2 Height	40.000 in (101.600 cm)
Package 2 Width	36.000 in (91.440 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	164.000 lb(US) (74.389 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**22 954 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**360 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**7 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**3 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**22 530 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**54 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**No**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant By Exemption**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**
PVC free	**No**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**95**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**