Product data sheet
Characteristics

170XTS00601
Modicon Momentum - busbar 1 rows - screw type terminals



Main

Range of Product	Modicon Momentum automation platform
Accessory / separate part designation	Busbar 1 row
Accessory / separate part type	Busbar
Accessory / separate part category	Connection accessories
Accessory / separate part destination	Discrete I/O base Analog I/O base
Product Specific Application	Serves as protective distribution connector Provides a common connection for the field devices
Connections - Terminals	Screw type terminals
Number of horizontal rows	1

Ordering and shipping details

Category	18206-MOMENTUM PROCESSORS,I/O BASES,CONN.
Discount Schedule	PC31
GTIN	3595861147850
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.91 in (2.3 cm)
Package 1 Width	0.47 in (1.2 cm)
Package 1 Length	4.53 in (11.5 cm)
Package 1 Weight	1.34 oz (38.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	180
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	15.85 lb(US) (7.19 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months