Product data sheet
Characteristics

9070MN500G0D1G13
Transformer disconnect, 500VA, 240x480VAC primary, 120VAC secondary, with outlet, compact Type 1

Main

Product	Transformer Disconnect
Certifications	UL Listed[RETURN]CSA
Enclosure Type	NEMA 1 mini
Insulation Temperature	356 °F (180 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	500 VA
Secondary Voltage	120 V
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Type	MN

Ordering and shipping details

Category	US10CP821694
Discount Schedule	0CP8
GTIN	785901313267
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.600 in (21.844 cm)
Package 1 Width	12.800 in (32.512 cm)
Package 1 Length	12.300 in (31.242 cm)
Package 1 Weight	24.000 lb(US) (10.886 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	18 months

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.