Product data sheet
Characteristics

8903SQH1V02
Contactor, Type S, multipole lighting, electrically held, 100A, 2 pole, 110/120 VAC 50/60 Hz coil, NEMA 3R



Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	2P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical Connection	Lugs
Height	25.3 in (643 mm)
Depth	8.6 in (219 mm)
Width	12.8 in (326 mm)

Environment

Enclosure Type	NEMA 3R Stainless Steel surface none
Product Certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901024033
Returnability	No

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.3 in (64.3 cm)
Package 1 Width	12.8 in (32.6 cm)
Package 1 Length	8.6 in (21.9 cm)
Package 1 Weight	9.753 lb(US) (4.424 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months