# Product data sheet
## Characteristics

# 9050JCK13V17
Timing Relay, Type JCK, plug In, on delay, adjustable time, 0.6 to 60 seconds, 10A, 240 VAC, 48 VAC/DC




## Main

| | |
|---|---|
| Product range | 9050JCK |
| Product type | Timer |
| Timing mode | On-delay |
| Timing range | 0.6...60 s |
| Supply voltage | 48 V AC/DC |

## Complementary

| | |
|---|---|
| Power consumption | 2 VA |
| Current rating | 10 A |
| Switch function | DPDT |
| Contact composition | 2 NO + 2 NC |
| Contact material | Silver nickel |
| Maximum switching voltage | 240 V AC |
| Mounting type | Socket |
| Number of pins | 8 |
| Shape of pins | Tubular |
| For use with | 8501NR51<br>8501NR52 |

## Environment

| | |
|---|---|
| Certifications | CE[RETURN]UL Listed[RETURN]UL Recognized |
| Ambient temperature range - operational | -18…150 °F (-28…66 °C) |
| Height | 2.40 in (61 mm) |
| Width | 1.69 in (43 mm) |
| Depth | 4.09 in (104 mm) |

## Ordering and shipping details

| | |
|---|---|
| Category | 21651-9050 JCK(NOT JCK60, 70) G P TIMERS |
| Discount Schedule | CP2 |
| Returnability | No |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.00 in (10.16 cm) |
| Package 1 Width | 2.00 in (5.08 cm) |
| Package 1 Length | 3.00 in (7.62 cm) |
| Package 1 Weight | 5.28 oz (149.685 g) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Green Premium product |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |