# Product data sheet
## Characteristics

# 9007C54CY1901
## Limit switch, 9007, 9007C 1 NO/NC, rotary head, CW+CCW, maintained



### Main

| | |
|---|---|
| Range of Product | 9007 |
| Series name | Heavy duty |
| Product or Component Type | Limit switch |
| Product Specific Application | Standard box |
| Device short name | 9007C |
| Body type | Plug-in |
| Head type | Rotary head |
| Material | Metal |
| Fixing Mode | By the body |
| Movement of operating head | Rotary |
| Type of operator | Zinc stay put without operating lever -)9007C lever |
| Switch actuation | CW and CCW<br>From left and right |
| Type of approach | Lateral approach, 1 direction programmable |
| Electrical connection | Male connector 7/8" - 16 UN - 2 A mini connector, 5 pins |
| Number of poles | 1 |
| Contacts type and composition | NC-NO |
| Contact operation | Snap action |
| Positive opening | Without |
| Sale per indivisible quantity | 1 |

### Complementary

| | |
|---|---|
| Body material | Zinc |
| Head material | Zinc |
| Function Available | - |
| Switch Function | SPDT-DB |
| Contact form | Form Z |
| Contacts material | Silver contacts |
| Terminals description ISO n°1 | (1-2)NC<br>(3-4)NO |
| Minimum torque for tripping | 3 lbf.in (0.34 N.m) |
| Maximum actuation speed | 90 Ft/Min with 45° cam angle, levers only<br>130 ft/min with 30° cam angle, levers only |
| Tripping angle | 45 ° |
| Maximum displacement angle | 90 ° |
| Repeat accuracy | +/- 0.002 in linear travel of cam |
| [Ie] rated operational current | 0.55 A 120 V DC<br>0.27 A 240 V DC<br>3 A 240 V AC NEMA<br>6 A 120 V AC NEMA |
| [Ithe] conventional enclosed thermal current | 6 A |
| [Ui] rated insulation voltage | 600 V 3)UL 508 contact block<br>600 V 3)CSA C22.2 No 14 contact block |
| [Uimp] rated impulse withstand voltage | 2.5 KV AC 1 min CE<br>2.2 KV AC 1 min UL<br>2.64 kV AC 1 s CSA |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|---|---|
| Short-circuit protection | 10 A CC non-time delay |
| Electrical durability | 1000000 cycles |
| Local signalling | without |
| Mechanical durability | 10000000 cycles |
| Width | 1.55 in (39.37 mm) |
| Height | 4.02 in (102.11 mm) |
| Depth | 2.5 in (63.50 mm) |
| Net Weight | 1.25 lb(US) (0.57 kg) |

## Environment

| | |
|---|---|
| Shock resistance | 60 gn 9 ms IEC 60068-2-27 |
| Vibration resistance | 25 gn 10…150 Hz)IEC 60068-2-6 |
| NEMA degree of protection | NEMA 1 Nema type 250<br>NEMA 2 Nema type 250<br>NEMA 4 Nema type 250<br>NEMA 6 Nema type 250<br>NEMA 6P Nema type 250<br>NEMA 12 Nema type 250<br>NEMA 13 Nema type 250 |
| IP degree of protection | IP67 conforming to IEC 60529 |
| Electrical shock protection class | Class 0 IEC 61140 |
| Ambient air temperature for operation | -20…185 °F (-29…85 °C) standard environment |
| Ambient Air Temperature for Storage | -20…185 °F (-29…85 °C) |
| Environmental characteristic | Standard environment |
| Protective treatment | Epoxy powder coat |

## Ordering and shipping details

| | |
|---|---|
| Category | 21499-9007 C LIMIT SWITCHES |
| Discount Schedule | DS1 |
| GTIN | 3606481724151 |
| Returnability | No |

## Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 10.16 in (25.806 cm) |
| Package 1 Width | 4.00 in (10.16 cm) |
| Package 1 Length | 25.81 in (65.548 cm) |
| Package 1 Weight | 20.00 oz (566.99 g) |

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Not applicable, out of EU RoHS legal scope |
| Environmental Disclosure | Product Environmental Profile |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |