# Product data sheet
## Characteristics

# EFB20P36C
## OEM Swbd Interior CU Single-Row Btm End-Fed 2000A 36H 24" Depth, 2 Ints/frame

### Main

| | |
|---|---|
| Range of Product | I-Line |
| Product or Component Type | Switchboard interior |

### Complementary

| | |
|---|---|
| [Ie] rated operational current | 2000 A |
| Bus material | Copper |
| Number of rows | 1 |
| Wire feed | Bottom |
| Height | 36 in (914.4 mm) |
| Width | 36 in (914.4 mm) |
| Depth | 24 in (609.60 mm) |
| Interior maximum breaker frame | 1200 A left side |
| Mounting space | 1)36 in (914.40 mm) left hand side |

### Ordering and shipping details

| | |
|---|---|
| Category | US1PE1A09483 |
| Discount Schedule | PE1A |
| Returnability | No |
| Country of origin | US |

### Packing Units

| | |
|---|---|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 22.50 in (57.15 cm) |
| Package 1 Width | 34.50 in (87.63 cm) |
| Package 1 Length | 90.0000000000 in (228.6 cm) |
| Package 1 Weight | 334.0006 lb(US) (151.5 kg) |

### Offer Sustainability

| | |
|---|---|
| EU RoHS Directive | Under investigation |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.