Product data sheet
Characteristics

CF16RJ63C36
OEM Swbd Interior CU Double-Row Ctr-Fed 1600A 63H 36" Depth 48" Width

Main

Range of Product	I-Line
Product or Component Type	Switchboard interior

Complementary

[Ie] rated operational current	1600 A
Bus material	Copper
Number of rows	2
Wire feed	Centre left side
Height	63 in (1600.2 mm)
Width	48 in (1219.20 mm)
Depth	36 in (914.40 mm)
Interior maximum breaker frame	250 A right side 1200 A left side
Mounting space	2)27 In (685.80 mm) left hand side 1)63 in (1600.20 mm) right hand side

Ordering and shipping details

Category	US1PE1A09484
Discount Schedule	PE1A
GTIN	3606487356059
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22.5 in (57.2 cm)
Package 1 Width	34.5 in (87.6 cm)
Package 1 Length	90.0000000000 in (228.6 cm)
Package 1 Weight	456.00 lb(US) (206.838 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.