


Note:
- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

XUDA2PSML2

Telemecanique Sensors

Telemecanique Sensors
1875 Founders Drive
Dayton, OH 45420-4017
Customer Care Center : 1-800-435-2121
Web : www.tesensors.com

Technical Information:

Diffuse with Background Suppression:	
Diffuse:	
Polarized Retroreflective:	
Thru Beam:	
Retroreflective:	
Circuit Type:	PNP
Output Mode:	Light/Dark Operate
Power:	DC
Voltage Range:	12-24 VDC
Max Load:	100 mA
Max Switching Frequency :	1000 or 5000 Hz
Temp Range:	-10° to 55° C (13° to 131° F)
NEMA Type:	4X (indoor use only)
IP Rating:	65
Standards:	UL, CE Rohs

Specification:

Sensor Type:	Fiber Amplifier
Description:	Photoelectric, Fiber Amplifier, DIN-rail, 12-24 VDC
Body Style:	DIN-rail
Diameter:	
Housing Material:	Plastic - PBT
Face Material:	PMMA
Adjustment:	Pushbutton fine teach
Cable Size:	2.0 m (6.6 ft)
Connector Type:	
Special Features:	Hinged cover