# Specification Sheet

Part Number: 558-00501

Continuous Polyester Labels are made with UV stable materials for long outdoor life.




Labels use UV stable permanent ink.

Continuous polyester is provided in continuous rolls so that the markers can be printed and cut to any length using HellermannTyton thermal trasnfer printing systems.

Adhesive Labels, Solid Color Continuous Roll, 1.0" x 250', UV Stable PET, Red, 250ft/roll

| | |
|---|---|
| Article Number | 558-00501 |
| Type | HT1RDHB250 |
| Color | Red (RD) |
| Quantity Per | reel |
| Product Description | Colored continuous rolls offer a high bond adhesive that is sustainable for low surface energy substrates such as the low density plastics on the front of an inverter or powder coat paint surfaces. The adhesive is designed to adhere to textured surfaces without peeling or falling off. |
| Short Description | Adhesive Labels, Solid Color Continuous Roll, 1.0" x 250', UV Stable PET, Red, 250ft/roll |

| | |
|---|---|
| Global Part Name | HT1RDHB250-840/281-RD |
| Length L (Imperial) | 250.0 |
| Length L (Metric) | 76.2 |
| Variant | 3.2mil, 50lb bleached kraft paper |
| Width W (Imperial) | 1.0 |
| Width W (Metric) | 25.4 |
| Width of Liner (Metric) | 25.4 |
| Width of Liner (Imperial) | 1.0 |
| Material | Type 840/281, Polyester, UV-stabilized, clear polyester laminate (840/281) |
| Material Shortcut | 840/281 |
| Adhesive | Acrylic |
| UV Resistant (Yes/No) | Yes |
| Adhesive Operating Temperature | -40°F to +302°F (-40°C to +150°C) |
| Operating Temperature | -40°F to +302°F (-40°C to +150°C) |

| | |
|---|---|
| Reach Compliant (Article 33) | No |
| ROHS Compliant | Yes |
| Certification/Specification | CSA 66956 UL 969 NEC2011 NEC2014 ANSI Standard Z535.4 IFC 2012 |
| UL Recognized (US) | Yes |
| Package Quantity (Imperial) | 250 |
| Package Quantity (Metric) | 76.20 |
| Customs Number | 3919102055 |
| Labels per Column | 1 |
| Labels per Row | 1 |

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 40 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2024 HellermannTyton. All Rights Reserved.