Product data sheet

Specifications



Con. M12, Female, Straight, 5 pins, 25 m pre wired

XZCP1164L25

Product availability : Non-Stock - Not normally stocked in distribution facility

Price* : 66.00 USD

Main

Range of product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessory
Accessory / Separate Part Type	Pre-wired connectors

Complementary

Electrical connection	Straight female connector M12, 5 pins (included earth pin)
Cable connector fixing	Screw-on
Collar material	Metal
Status LED	Without
Cable length	82.02 ft (25 m)
Cable outer diameter	0.23 in (5.9 mm)
Cable composition	5 x 0.34 mm²
Wire insulation material	PUR
[Ue] rated operational voltage	30 V AC 36 V DC
Line Rated Current	4 A
Contact resistance	5000 µOhm
Minimum insulating resistance	1 GΩ

Environment

IP degree of protection	IP65 IP69K IP67
Product Certifications	cULus
Ambient air temperature for operation	-40…176 °F (-40…80 °C) static 23…176 °F (-5…80 °C) flexing
Ambient Air Temperature for Storage	-40…176 °F (-40…80 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES

* Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Discount Schedule	DS3
GTIN	03389119620437
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	Yes
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.68 in (6.8 cm)
Package 1 width	9.02 in (22.9 cm)
Package 1 Length	8.98 in (22.8 cm)
Unit Type of Package 2	S02
Number of Units in Package 2	5
Package 2 Weight	10.00 lb(US) (4.536 kg)
Package 2 Height	5.91 in (15 cm)
Package 2 width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 3 Height	5.91 in (15 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes