Rittal – The System.

Faster – better – everywhere.

NH fuse-switch disconnector, size 00 to 3 – SV 9343.110

Date : May 29, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

NH fuse-switch disconnector, size 00 to 3 – SV 9343.110

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Material:	Polyamide (PA 6) Fire protection corresponding to UL 94-V0 Contact tracks: Electrolytic copper, silver-plated
Color:	Chassis: RAL 7035 Cover: RAL 7035/7001
Basis of test:	IEC 60 947-3 IEC 60 269-2 (fuse inserts)
Note:	The technical data may vary in the case of UR applications. UR applications only in conjunction with "Special Purpose Fuses".

Product features

Version:	Size: 1
Suitable for busbars:	with cross-section height: 5 mm (0.2 ″) with cross-section height: 10 mm (0.39 ″)
Number of poles:	3-pole
For bar systems with center-to-center spacing:	60 mm
Dimensions:	Height: 298 mm (12 ″) Width: 184 mm (7.2 ″)
Type of connection	Screw M10

© Rittal 2018

(electrical):	
Rated operating voltage:	690 V, 3~
Clamping area for laminated copper bars::	Height: 10 mm (0.39 ″) Width: 32 mm (1.3 ″)
Connection for round conductor cross-sections:	10 mm² - 150 mm²
Rated operating current max.:	250 A
Cable outlet:	Top/bottom
Packaging unit:	1 pc(s).
Weight/packaging unit:	2.26 kg (5 lb.)
EAN:	4028177540330
Customs tariff number:	85369095
ETIM 6.0:	EC001040
ETIM 5.0:	EC001040
eCl@ss 8.0/8.1:	27371401
eCl@ss 7.0/7.1:	27371401
eCl@ss 6.0/6.1:	27371401
eCl@ss 5.1/5.1.4:	27370302
Product description (long):	SV NH fuse-switch disconnector, size 1, 250 A, 690 V , 3-pole, screw M10

Approvals

Approvals:	C-UR UR
Certificates:	EAC
Declarations:	Declaration of conformity