GE Lighting

75399 - F40/25BX830IS/WM

GE Biax® T5 - Facilities; Hospitality; Office; Restaurant; Retail Display; Warehouse

High Color Rendering
Energy Savings







GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Equivalent Wattage (NOM)	100.0 W
Rated Life (NOM)	20000.0 h
Starting Temperature (MIN)	10.0 °C
Mercury Content (NOM)	4.0 mg
Picograms of Mercury (NOM)	96.2 pg
Additional Info	TCLP compliant
Primary Application	Facilities;Hospitality;Office;Restaurant;R Display;Warehouse

PHOTOMETRIC CHARACTERISTICS

Initial Lumens (NOM)	2600.0
Mean Lumens (NOM)	2400.0
Nominal Initial Lumens per Watt (NOM)	104.0
Color Temperature (NOM)	3000.0 K
Color Rendering Index (CRI) (NOM)	82.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	25.0
Voltage (NOM)	120.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	21.500 in(546.1 mm)
Nominal Length (NOM)	21.500 in(546.1 mm)

PRODUCT INFORMATION

Product Code	75399
Description	F40/25BX830IS/WM
ANSI Code	60901-IEC-6240-2
Standard Package	Master
Standard Package GTIN	10043168753996
Standard Package Quantity	40
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	40
UPC	043168753999

CAUTIONS & WARNINGS

Caution

• Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

NOTES

• 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

• Fluorescent lamp lumens decline during life