Rittal – The System.

Faster – better – everywhere.

TopTherm Filter Fan Units EMC – SK 3238.600

Date : May 29, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

TopTherm Filter Fan Units EMC – SK 3238.600

created: 29.05.2018 build on www.rittal.com/us-en



Product description

Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 54 with standard filter and hose-proof hood: IP 56 with standard filter and additional fine filter mat: IP 54
Protection category NEMA:	NEMA 12 with hose-proof hood: NEMA 3 with hose-proof hood: NEMA 3R with hose-proof hood: NEMA 4 with hose-proof hood: NEMA 4X with standard filter and hose-proof hood: NEMA 12
Supply includes:	Complete unit ready for connection, including filter mat
Note:	For energy-efficient operation of the filter fan units, we recommend using the enclosure internal thermostat, the speed control or the digital enclosure internal temperature display and thermostat.

Product features

Air throughput (unimpeded air flow):	At 50 Hz: 55 m³/h (32.4 cfm) At 60 Hz: 66 m³/h (38.8 cfm)
Air throughput with outlet filter, including standard filter mat (quantity x order number, throughput 50/60 Hz):	1 x 3238060: 43/50 m³/h 2 x 3238060: 46/56 m³/h
Rated operating	230 V, 1~, 50 Hz/60 Hz

voltage:	
Dimensions:	Height: 148.5 mm (5.8 ″) Width: 148.5 mm (5.8 ″)
Required mounting cut-out:	Height: 124 mm (4.9 ″) Width: 124 mm (4.9 ″)
Build depth:	16 mm (0.63 ″)
Installation depth:	58.5 mm (2.3 ″)
Temperature range:	Storage: -30°C...+70°C Operation (environment): -10°C...+55°C
EMC version:	yes
Rated power Pel:	At 50 Hz: 19 W At 60 Hz: 18 W
Rated current (max.):	At 50 Hz: 0.12 A At 60 Hz: 0.11 A
Miniature circuit-breaker/fuse:	2 A
Noise pressure level:	At 50 Hz: 46 dB(A) At 60 Hz: 49 dB(A)
Diagonal fan:	Diagonal, self-starting shaded pole motor
Packaging unit:	1 pc(s).
Weight/packaging unit:	2 kg (4.4 lb.)
EAN:	4028177652439
Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705

Product description (long):	SK fan and filter units TopTherm, 55/66 m³/h, 230 V, 1~, 50/60 Hz, WHD: 148.5 x 148.5 x 16 mm, EMC

Approvals

Approvals:	Approval overview CSA UL + C-UL - FTTA UR + C-UR
Certificates:	EAC
Declarations:	Declaration of conformity