Rittal – The System.

Faster – better – everywhere.

# FlatBox – DK 7507.110

Date : May 24, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# FlatBox – DK 7507.110

created: 24.05.2018 build on www.rittal.com/us-en



## Product description

| | |
|---|---|
| **Version:** | with 19" mounting rails |
| **Description:** | For flexible use as a wall-mounted or floor-standing enclosure. |
| **Benefits:** | Tool-free quick mounting<br>System accessories on the open 19" frame |
| **Material:** | Carbon steel<br>Viewing window: Single-pane safety glass, 3 mm |
| **Surface finish:** | Powder-coated |
| **Color:** | RAL 7035 |
| **Supply includes:** | Flat-packed enclosure<br>1 wall section<br>2 basic supports<br>2 roof/base plates, with cut-outs for cable entry via brush strips<br>2 side panels, lockable<br>1 glazed door, lockable, security lock 3524 E, door catch freely selectable<br>Connection components for tool-free, fast assembly<br>Grounding kit for system-compatible grounding of all enclosure parts<br>19" profile rails |
| **Note:** | Max. installation depth: Depth - 58 mm to rear panel<br>Max. distance between two 19" levels: Depth - 104 mm |
| **Base material:** | Carbon steel |

## Product features

| | |
|---|---|
| **Dimensions:** | Height: 492 mm (19 ″)<br>Width: 600 mm (24 ″)<br>Depth: 600 mm (24 ″) |
| **Installation height for components:** | 9 U (9 U) |
| **Packaging unit:** | 1 pc(s). |
| **Weight/packaging unit:** | 27 kg (59.5 lb.) |
| **EAN:** | 4028177551442 |
| **Customs tariff number:** | 94032080 |
| **ETIM 6.0:** | EC002500 |
| **ETIM 5.0:** | EC002500 |
| **eCl@ss 8.0/8.1:** | 27180208 |
| **eCl@ss 7.0/7.1:** | 27180208 |
| **eCl@ss 6.0/6.1:** | 27180208 |
| **eCl@ss 5.1/5.1.4:** | 27180204 |
| **Product description (long):** | DK FlatBox, WHD: 600x492x600 mm, 9 U, with 482.6 mm (19") mounting angles |