Rittal – The System.

Faster – better – everywhere.

Mini-Fan – SK 3236.124

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Mini-Fan – SK 3236.124

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Description:	Compact DC fan for enclosure and component cooling in enclosures.
Supply includes:	Fans Fastening Screws Contact Hazard Protection

Product features

Air throughput (unimpeded air flow):	21 m³/h (12.4 cfm)
Unimpeded air flow (without filter mats):	
Unimpeded air flow (with filter mats):	
Rated operating voltage:	24 V (DC)
Dimensions:	Height: 60 mm (2.4 ″) Width: 60 mm (2.4 ″) Depth: 25.4 mm (1 ″)
Temperature range:	Operation (environment): -20°C...+70°C
Rated power Pel:	with DC: 1 W
Noise pressure level:	with DC: 20 dB(A)
Packaging unit:	1 pc(s).

Weight/packaging unit:	0.14 kg (0.3 lb.)
EAN:	4028177637603
Customs tariff number:	84145915
ETIM 6.0:	EC000320
ETIM 5.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 7.0/7.1:	27180716
eCl@ss 6.0/6.1:	27180716
eCl@ss 5.1/5.1.4:	27180705
Product description (long):	SK Mini fan, 1 W, 24 V (DC), WHD: 60 x 60 x 25.4 mm

Approvals

Approvals:	Approval overview UR
Certificates:	EAC