Rittal – The System.

Faster – better – everywhere.

Optipanel – CP 6380.000

Date : May 25, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Optipanel – CP 6380.000

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Version:	Support arm connection, rectangular 120 x 65 mm
Benefits:	Aluminum housing, high thermal conductivity for optimum passive heat dissipation. Low weight coupled with high stability Compatible with all Rittal stand and support arm systems
Material:	Housing: Extruded aluminum section Corner pieces: Die-cast zinc Corner protectors: Plastic
Color:	Housing: Natural anodized. Corner pieces: RAL 7035 Corner protectors: Similar to RAL 7024
Protection category IP to IEC 60 529:	IP 65
Supply includes:	Housing with hinged rear panel Seals
Note:	The support arm connection may be swapped over by rotating the enclosure 3 mm double-bit lock insert may be exchanged for 41 mm lock inserts, plastic handles and T handles, type C Rear panel hinges on the longest enclosure side

Product features

For the configuration of subracks:	Suitable for front panel width: 482.6 mm (19 ″)
Installation depth:	100 mm (3.9 ″)

Â© Rittal 2018

Suitable for front panels:	with height: 310.3 mm (12 ″) with width: 482.6 mm (19 ″)
Lock version:	Cam
No. of locks:	2
Lock Insert:	3 mm double-bit
Packaging unit:	1 pc(s).
Weight/packaging unit:	6.2 kg (13.7 lb.)
EAN:	4028177231627
Customs tariff number:	94032080
ETIM 6.0:	EC002504
ETIM 5.0:	EC002504
eCl@ss 8.0/8.1:	27180505
eCl@ss 7.0/7.1:	27180505
eCl@ss 6.0/6.1:	27180505
eCl@ss 5.1/5.1.4:	27180505
Product description (long):	CP Optipanel, for front panel BH 482,6x310,3 mm, installation depth 100 mm, Extruded aluminum section, Support arm connection 120x65 mm

Approvals

Approvals:	UL + C-UL
Declarations:	Declaration of conformity