GE Lighting

# 97572 - F13BX/850/ECO


GE Ecolux® Biax® T4 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

High Color Rendering
Energy Savings











## GENERAL CHARACTERISTICS

| | |
|---|---|
| Lamp Type | Compact Fluorescent - Plug-In |
| Bulb | T4 |
| Base | GX23 |
| Equivalent Wattage (NOM) | 60.0 W |
| Rated Life (NOM) | 10000.0 h |
| Starting Temperature (MIN) | 0.0 °C |
| Mercury Content (NOM) | 3.0 mg |
| Picograms of Mercury (NOM) | 444.4445 pg |
| Additional Info | TCLP compliant |
| Primary Application | Standard;Facilities;Retail Display;Hospitality;Office;Restaurant;Wa |

## PHOTOMETRIC CHARACTERISTICS

| | |
|---|---|
| Initial Lumens (NOM) | 784.0 |
| Mean Lumens (NOM) | 675.0 |
| Nominal Initial Lumens per Watt (NOM) | 60.30769 |
| Color Temperature (NOM) | 5000.0 K |
| Color Rendering Index (CRI) (NOM) | 80.0 |

## ELECTRICAL CHARACTERISTICS

| | |
|---|---|
| Wattage (NOM) | 13.0 |
| Voltage (NOM) | 59.0 |
| Lamp Current (NOM) | 0.285 A |
| Current Crest Factor (MAX) | 1.7 |
| Supply Current Frequency (NOM) | 60.0 Hz |

## DIMENSIONS

| | |
|---|---|
| Maximum Overall Length (MOL) (NOM) | 7.300 in(185.4 mm) |
| Nominal Length (NOM) | 7.000 in(177.8 mm) |
| Base Face to Top of Lamp (NOM) | 6.690 in(169.9 mm) |

## PRODUCT INFORMATION

| | |
|---|---|
| Product Code | 97572 |
| Description | F13BX/850/ECO |
| ANSI Code | 60901-IEC-0013-1 |
| Standard Package | BUNDLE |
| Standard Package GTIN | |
| Standard Package Quantity | 100 |
| Sales Unit | Unit |
| No Of Items Per Sales Unit | 1 |
| No Of Items Per Standard Package | 100 |
| UPC | 043168975728 |

### CAUTIONS & WARNINGS

**Caution**

• Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

### NOTES

• Based on 60Hz reference circuit.
• Fluorescent lamp lumens decline during life