Rittal – The System.

Faster – better – everywhere.

Signal pillar, LED compact – SG 2372.100

Date : May 25, 2018

ENCLOSURES POWER DISTRIBUTION CLIMATE CONTROL IT INFRASTRUCTURE SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Signal pillar, LED compact – SG 2372.100

created: 25.05.2018 build on www.rittal.com/us-en



Product description

Description:	Angle of reflected beam: 3 x 120°, as delivered: Steady light. Flashing function PLC controllable
Benefits:	Complete, ready-to-connect solution Minimal build height Long service life of the LEDs Minimal assembly work and warehousing costs
Protection category IP to IEC 60 529:	IP 65

Product features

Dimensions:	Height: 177 mm (7 ″) Diameter: 72 mm
Rated operating voltage:	24 V 24 V (DC)
Diameter:	72 mm
Operating temperature:	Operation (environment): -20°C...+70°C
Type of connection (electrical):	Screw clamps
Equipment (electrical):	Light (bulb): LEDs
Rated insulation voltage:	< 60 V DC

© Rittal 2018

Cable entry:	Metric diameter: M12 x 1.5 For cable diameter: 3 mm - 6,5 mm
Packaging unit:	1 pc(s).
Weight/packaging unit:	0.34 kg (0.7 lb.)
EAN:	4028177442719
Customs tariff number:	85318070
ETIM 6.0:	EC001042
ETIM 5.0:	EC001042
eCl@ss 8.0/8.1:	27371230
eCl@ss 7.0/7.1:	27371230
eCl@ss 6.0/6.1:	27371230
eCl@ss 5.1/5.1.4:	27371220
Product description (long):	SG Signal pillar, LED-compact, 24 V AC/DC, 3-stage, red/amber/green

Approvals

Approvals:	C-UL UR
Certificates:	EAC
Declarations:	Declaration of conformity