

TOUCH™ WI-FI READY REMOTE SWITCH, MAGNESIUM

ASTHRRM1 | adorne

FEATURES & BENEFITS

USAGE

• Perfect anywhere you'd like to combine Wi-Fi-Ready lighting control with sleek, recognizable touch technology.
• The Touch Wi-Fi Ready Remote Switch is a programmable light switch that pairs with the adorne Hub and the Touch Wi-Fi Ready Master Switch to create smart lighting solutions for your home.
• Turn lights on and off with the touch of a finger – or create custom lighting settings to control lights from your smartphone or tablet via the Legrand Lighting Control app.
• This item is also available in white.

*HGTV, HGTV Smart Home, HGTV Smart Home Giveaway and their associated logos are trademarks of Scripps Network, LLC. Used with permission, all rights reserved

GETTING STARTED

• Time to install: 25 minutes or less.
• The Touch Wi-Fi Ready Remote Switch lets you control a light from a new location without running new wires. Simply install and pair with the Touch Wi-Fi Ready Master Switch via the easy-to-follow instructions and enjoy customizable control of a single lighting source from two locations or your smartphone.
• The Legrand Lighting Control app is available for free on iTunes and Google Play.
• This item requires the adorne Hub. Shop now to learn how Wi-Fi lighting solutions can transform your home.
• This item requires an adorne Wall Plate. Shop now to choose from dozens of finishes including a variety of luxurious metals, or order in your own custom finish.
• Looking to integrate other party advanced automation systems? Visit our partners page.

SPECIFICATIONS

GENERAL INFO

Color: Magnesium
Product Series: adorne Touch
Style: Touch

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

cULus: Yes
FCC Standard: Yes
UL Listing No: UL 508

UL Standard: Yes
UN SPSC: 39121107

DIMENSIONS

Depth (US): 1.63"
Height (US): 4.185"
Length (US): 2.66"
Width (US): 1.77"
Product Weight (US): 0.18 pounds

TECHNICAL INFORMATION

AC Voltage Output: 120VAC
Frequency: 900 MHz (RF)
Humidity: 0-80% relative humidity, noncondensing
Material: FR4(PCB)
Mounting: USA Electrical Wiring Box / adorne Mounting Plate
Operating Temperature (Celsius): 0°C to 50°C
Storage Temperature: 32°F to 122°F
Watts: Auxiliary Remote - No Load