SIEMENS

Data sheet US2:52PA8B3

Metal, pushbutton 2 position Operator only Momentary Extended, green Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

Design of the product	Actuator round
Enclosure	
Number of command points	1
Delivery state	
• as a kit	No
Actuator	
Design of the operating mechanism	Pushbutton
Material of the actuating element	plastic
Shape of the actuating element	Raised pushbutton
Type of unlocking device	without
Number of switching positions	2
Front ring	
Product component front ring	Yes
Design of the front ring	standard
Material of the front ring	metal
Color of the front ring	chrome

Subject to change without notice
© Copyright Siemens

Holder	
Material of the holder	Metal

General technical data	
Product component	
• Light source	No
Degree of pollution	1
Protection class IP	IP66

Ambient conditions	
Ambient temperature	
• during operation	-35 ... +70 °C
• during storage	-40 ... +85 °C

Installation/ mounting/ dimensions	
Shape of the installation opening	round

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,…)
www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PA8B3

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PA8B3

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/US2:52PA8B3

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PA8B3&lang=en

last modified: 11/13/2019

Subject to change without notice
© Copyright Siemens