
GE Lighting


24756 - 4541

GE PAR56 - Aircraft











GENERAL CHARACTERISTICS

Lamp Type	Sealed Beam - PAR
Bulb	PAR56
Base	Screw Terminals
Filament	C-13
Rated Life (NOM)	25.0 h
Primary Application	Aircraft

PHOTOMETRIC CHARACTERISTICS

Beam Spread - Horizontal	15.0 - 10.0 °
Beam Spread - Vertical	11.0 - 10.0 °
Max. Beam Candlepower (MBCP) (MAX)	470000.0

ELECTRICAL CHARACTERISTICS

Wattage (NOM)	450.0
Voltage (NOM)	28.0

DIMENSIONS

Maximum Overall Length (MOL) (NOM)	4.500 in(114.3 mm)
Bulb Diameter (DIA) (NOM)	7.000 in(177.8 mm)

PRODUCT INFORMATION

Product Code	24756
Description	4541
ANSI Code	4541
Standard Package	Case
Standard Package GTIN	10043168247563
Standard Package Quantity	12
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	12
UPC	043168247566

CAUTIONS & WARNINGS

Warning

- Unexpected lamp rupture may cause injury, fire, or property damage
  - Avoid direct water/liquid contact.
  - Avoid contact with glass during operation.
- Risk of Fire
  - Keep combustible materials away from lamp.
  - Use in fixture rated for this product.

NOTES

- Filament shielded.