GE Lighting

63097 - GEC226-MVPS-3W

High frequency electronic ballasts for 2 or 1 CFL lamps

- Line Voltage: Multi-Voltage 120 to 277 VAC, +/-10%, 50-60Hz
- Series Lamp Operation
- IC Control
- Programmed starting for extended lamp life
- Active Power Factor Correction

cUL Listed

UL Listed

*GE Lighting warrants to the purchaser that each electronic ballast will be free from defects in material or workmanship for a period of 5 years from the date of manufacture when properly installed and under normal conditions of use.

GENERAL CHARACTERISTICS

Lamp Type	Fluorescent -
Bulb	Electronic
Ballast Type	High Frequency Electronic Ballasts
Starting Method	Programmed start
Lamp Wiring	Series
Line Voltage Regulation (+/-)	10.0 %
Ambient Temperature (MIN)	-29.0 °C
Ambient Temperature (MAX)	40.0 °C
Ballast Factor	High (1.15)
Power Factor Correction	Active
Sound Rating	A (20-24 decibels)
Enclosure Type	Metal Can

ELECTRICAL CHARACTERISTICS

Supply Current Frequency	50.0 Hz

DIMENSIONS

Weight	0.419 lb
Exit Type	

PRODUCT INFORMATION

Product Code	63097
Description	GEC226-MVPS-3W
Standard Package	03-Master
Standard Package GTIN	10043168630976
Standard Package Quantity	10
Sales Unit	Pallet
No Of Items Per Sales Unit	10
No Of Items Per Standard Package	10
UPC	043168630979

NOTES

- Install and Ground Per National Electric Code
- Insulate unused blue lead for 600 VRMS.