



Architektur 2" LED Downlight Accessories

- D2ICAT is Ideal for insulated ceilings
- Secondary support for D2LED
- D2LED available for 5 Day Quick-Ship

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1437200	D2FRM	785235429986	Optional Mounting Frame for D2LED	●		●	●		3.5	2
BG1578400	D2CP	785235432238	Chicago Plenum housing for use with D2LED			●			7.5	1

QS75 5-Day Quick-Ship Ordering Guide Order Limit Per Luminaire Selection: 20 Pieces or Less									
D2LED		2D9LED	9L	30K	8	MD25			
J-TUBE ASSEMBLY	VOLTAGE	LIGHT ENGINE	OUTPUT	LED COLOR	CRI	BEAM ANGLE	REFLECTOR FINISH	REFLECTOR COLORS	
D2LED 2" J-Tube Assembly with 0-10 Dimming standard	Blank 120V 277 277V	2D9LED 2" Open Reflector/ Light Engine Assembly	9L 900 Lumens 12L 1200 Lumens	30K 3000 Kelvin 35K 3500 Kelvin	8 Nominal 80+ CRI	WFL45 Spun Aluminum reflector with a 45° wide flood distribution MD25 Spun Aluminum reflector with a 25° medium distribution FL35 Spun Aluminum reflector with a 35° flood distribution WW Wall Wash	Blank Specular	Blank Clear Alzak	

*Reflector finishes other than clear specular are not QS items.

QS710 10-Day Quick-Ship Ordering Guide Order Limit Per Luminaire Selection: 50 Pieces or Less										
D2LED		2D9LED	9L	30K	8	MD25				WT
J-TUBE ASSEMBLY	VOLTAGE	LIGHT ENGINE	OUTPUT	LED COLOR	CRI	BEAM ANGLE	REFLECTOR FINISH	REFLECTOR COLORS	REFLECTOR OPTIONS	
D2LED 2" J-Tube Assembly with 0-10 Dimming standard	Blank 120V 277 277V	2D9LED 2" Open Reflector/ Light Engine Assembly	9L 900 Lumens 12L 1200 Lumens	30K 3000 Kelvin 35K 3500 Kelvin	8 Nominal 80+ CRI	WFL45 Spun Aluminum reflector with a 45° wide flood distribution MD25 Spun Aluminum reflector with a 25° medium distribution FL35 Spun Aluminum reflector with a 35° flood distribution WW Wall Wash	Blank Specular	Blank Clear Alzak	WT White trim	

*Reflector finishes other than clear specular are not QS items.

QS710

10-Day Quick-Ship Ordering Guide

Order Limit Per Luminaire Selection: 50 Pieces or Less

A2LED

J-TUBE ASSEMBLY

A2LED 2" J-Tube Assembly with 0-10 Dimming standard

VOLTAGE

Blank 120V 277 277V

2A9LED

LIGHT ENGINE

2A9LED 2" Open Reflector/ Light Engine Assembly

9L

OUTPUT

9L 900 Lumens 12L 1200 Lumens

30K

LED COLOR

30K 3000 Kelvin 35K 3500 Kelvin

8

CRI

8 Nominal 80+ CRI

MD25

BEAM ANGLE

FL35 Spun Aluminum reflector with a 35° flood distribution

LOWER REFLECTOR FINISH

Blank Specular

LOWER REFLECTOR COLORS

Blank Clear Alzak

LOWER REFLECTOR OPTIONS

WT White trim

LOWER REFLECTOR ANGLE CUT

Blank Standard slot to accomodate 30° aiming

WT

*Reflector finishes other than clear specular are not QS items.



ENERGY STAR

LiteFrame® 4" & 6" LED Square Housing

• Commercial grade LED square downlight

• Minimum 50,000 hours at 70% lumen maintenance

• ENERGY STAR® Qualified

• Color consistency using remote phosphor technology


Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1501400	LF4SQSL	785235430142	4" housing, High Efficacy LED Square with 0-10V dimming to 10%	●	●	●	●	●	6.45	2	●
BG1501500	LF4SQSLWW	785235430159	4" housing, High Efficacy LED Square Wall Wash with 0-10V dimming to 10%		●				6.45	1	
BG1501600	LF6SQSL	785235430166	6" High Efficacy LED Square Housing with 0-10V dimming to 10%	●		●			5.64	2	●
BG1501700	LF6SQSLWW	785235430173	6" High Efficacy LED Square Wall Wash Housing wiht 0-10V dimming to 10%	●					5.66	1	

QS710

10-Day Quick Ship Ordering Guide

Order Limit Per Fixture Selection: 50 Pieces or Less

All Non Stocked LiteFrame Squares LED Housings are Quick Ship. Except HDM & 2DM



Architektur 6" Triple Tube Horizontal Housings, Multi-volt Electronic Ballasts and Trims

• Virtual Source® optics


• Electronic ballast standard

• Chicago Plenum (CP) option available, see specification sheet

• Damp Listed

• UL, CSA listed for damp locations

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BE827500	CFT632HEB	785235221078	6" housing, 1-lamp, 26/32/42W			●			6.6	1
BG1227900	STF602H	785235046947	6" Self trim clear Alzak			●			0.7	1



Architektur 6" Vertical Triple Tube Housings with Multi-volt Electronic Ballast and Trims

• Virtual Source® optics

• Electronic ballast standard

• Chicago Plenum (CP) option available, see specification sheet

• Damp Listed

• UL, CSA listed for damp locations

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG123600	CFT632EB	785235051071	6" housing, 1-lamp, 26/32/42W		●				5.3	2
BE681800	STF602	785235101363	6" Self trim clear Alzak		●				0.9	1

All Non-Stocked Architektur Standard, DM & EM Only 4", 6" & 8" Horizontal and Vertical CFL Housings & Clear Spec Trims are Quick Ship.



ENERGY STAR

LiteFrame® 4" LED Housing and Trims

• Commercial grade LED downlight

• Minimum 50,000 hours at 70% lumen maintenance

• ENERGY STAR® Qualified

• Color consistency using remote phosphor technology

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1500800	LF4SL	785235430081	4" housing, High Efficacy LED with 0-10V dimming to 10%	●	●	●	●	●	6.6	2	●
BG1512900	LF4SLEMR	785235430708	4" housing, High Efficacy LED with Remote Emergency Battery Pack, 0-10V dimming to 10%	●			●	●	10.68	1	
BG1580800	4LFSL11L35K	785235432443	4" Open Reflector/LED Light Engine Assembly, 1100 lumens, 3500 Kelvin with clear reflector	●	●	●	●	●	3.03	1	●
BG1581100	4LFSL11L35KWT	785235432450	4" Open Reflector/LED Light Engine Assembly, 1100 lumens, 3500 Kelvin with clear reflector and white trim	●			●		4.4	1	●
BG1581000	4LFSL20L35K	785235432467	4" Open Reflector/LED Light Engine Assembly, 2000 lumens, 3500 Kelvin with clear reflector	●	●	●			4.4	1	●
BG1571600	LF4SLCP	785235431385	4" CP Housing, High Efficacy LED with 0-10V dimming to 10%			●			16.0	1	

QS710

10-Day Quick Ship Ordering Guide

Order Limit Per Fixture Selection: 50 Pieces or Less





Retroficient™ 6" LiteFrame® Commercial LED Housing and Trims


- Glare free optical control
- 1000-1800 Lumens delivered
- Easy installation from below the ceiling
- ENERGY STAR® Qualified

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1577400	RLC6SL	785235432214	6" Standard Lumen LED Retrofit Housing, 120V-277V, Non-Dimming	●					4.66	1	●
BG1577500	RLC6SLDM	785235432221	6" Standard Lumen LED Retrofit Housing, 120V-277V, 0-10V 10% Dimming	●					4.66	1	●
BG1569200	6LCSL10L35K8	785235431606	6" Standard Lumen Commercial LED Light Engine Assembly, 1000 Lumen, 3500 Kelvin, 80 CRI, clear reflector	●	●	●		●	1.72	1	●
BG1569300	6LCSL14L35K8	785235431613	6" Standard Lumen Commercial LED Light Engine Assembly, 1400 Lumens, 3500 Kelvin, 80 CRI, clear reflector	●	●	●		●	1.72	1	●
BG1569400	6LCSL18L35K8	785235431620	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 3500 Kelvin, 80 CRI, clear reflector	●	●	●		●	1.72	1	●
BG1569500	6LCSL10L40K8WT	785235431637	6" Standard Lumen Commercial LED Light Engine Assembly, 1000 Lumens, 4000 Kelvin, 80 CRI, clear reflector and white trim		●				1.72	1	●
BG1569600	6LCSL10L35K8WT	785235431644	6" Standard Lumen Commercial LED Light Engine Assembly, 1000 Lumens, 3500 Kelvin, 80 CRI, clear reflector and white trim	●	●			●	1.72	1	●
BG1569700	6LCSL14L35K8WT	785235431651	6" Standard Lumen Commercial LED Light Engine Assembly, 1400 Lumens, 3500 Kelvin, 80 CRI, clear reflector and white trim	●	●			●	1.72	1	●
BG1569800	6LCSL18L35K8WT	785235431668	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 3500 Kelvin, 80 CRI, clear reflector and white trim	●	●	●		●	1.72	1	●
BG1569900	6LCSL14L35K8WH	785235431675	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 3500 Kelvin, 80 CRI, white reflector and white trim	●	●			●	1.47	1	
BG1570000	6LCSL18L40K8	785235431682	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 4000 Kelvin, 80 CRI, clear reflector			●		●	1.72	1	●
BG1570100	6LCSL14L40K8	785235431699	6" Standard Lumen Commercial LED Light Engine Assembly, 1400 Lumens, 4000 Kelvin, 80 CRI, clear reflector			●			1.72	1	●



10-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 50 Pieces or Less

All Non Stocked Retroficient LiteFrame Commercial Housings including 8” models are Quick Ship.





Retroficient™ 6" LiteFrame® LED Housing and Trims

- Minimum 50,000 hour at 70% lumen maintenance system life
- ENERGY STAR® Qualified
- Easy installation from below the ceiling
- Over 70 lumens per watt delivered
- CSA listed for wet locations and through wiring

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1501800	RLF6SL	785235430180	6" housing, High Efficacy LED Retrofit with 0-10V dimming to 10%	●	●			●	5	1	●
BG1580700	6LFSL11L35K	785235432474	6" Open Reflector/LED Light Engine Assembly, 1100 lumens, 3500 Kelvin, clear reflector	●	●	●	●	●	3	1	●
BG1581200	6LFSL11L35KWT	785235432481	6" Open Reflector/LED Light Engine Assembly, 1100 lumens, 3500 Kelvin, clear reflector and white trim	●	●		●	●	3	1	●
BG1581400	6LFSL15L35K	785235432498	6" Open Reflector/LED Light Engine Assembly, 1500 lumens, 3500 Kelvin, clear reflector	●	●			●	3	1	●
BG1581500	6LFSL15L35KWT	785235432504	6" Open Reflector/LED Light Engine Assembly, 1500 lumens, 3500 Kelvin, clear reflector and white trim	●				●	3	1	●
BG1580900	6LFSL20L35K	785235432511	6" Open Reflector/LED Light Engine Assembly, 2000 lumens, 3500 Kelvin, clear reflector	●	●	●		●	3	1	●
BG1581300	6LFSL20L35KWT	785235432528	6" Open Reflector/LED Light Engine Assembly, 2000 lumens, 3500 Kelvin, clear reflector and white trim	●	●	●	●	●	3	1	●
BG1581600	6LFSL20L40K	785235432535	6" Open Reflector/LED Light Engine Assembly, 2000 lumens, 4000 Kelvin, clear reflector	●		●		●	3	1	●
BG1581700	6LFSL20L40KWT	785235432542	6" Open Reflector/LED Light Engine Assembly, 2000 lumens, 4000 Kelvin, clear reflector and white trim	●				●	3	1	●





Retroficient™ 8" LiteFrame® LED Housing and Trim

- Minimum 50,000 hour at 70% lumen maintenance system life
- ENERGY STAR® Qualified
- Easy installation from below the ceiling
- Over 70 lumens per watt delivered
- CSA listed for wet locations and through wiring

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1501900	RLF8SL	785235430197	8" housing, High Efficacy LED Retrofit with 0-10V dimming to 10%	●	●	●	●	●	5	1	●
BG1581800	8LFSL20L35K	785235432559	8" Open Reflector/LED Light Engine Assembly, 2000 lumens, 3500 Kelvin, clear reflector	●				●	3.5	1	●



10-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 50 Pieces or Less

All Non Stocked Retroficient LiteFrame LED Housings are Quick Ship. Except HDM & 2DM





LiteFrame® Commercial LED 6" & 8" Housings and Trims

• 1000-4000 Lumens delivered

• Minimum 50,000 hour at 70% lumen maintenance system life

• ENERGY STAR® Qualified

• Non-IC rated. Suitable for wet locations and through branch wiring

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1577200	LC6SL	785235432115	6" Standard Lumen LED Housing, 120V-277V Non-Dimming	●	●	●		●	5.58	2	●
BG1577300	LC6SLDM	785235432108	6" Standard Lumen LED Housing, 120V-277V 0-10V 10% Dimming	●	●	●		●	5.58	2	●
BG1577600	LC6SLDMEM	785235432122	6" Standard Lumen LED Housing 120V-277V 0-10V Dimming, Battery Backup	●				●	11.125	1	
BG1578000	LC6SLCP	785235432085	6" Standard Lumen LED Housing, 120V-277V Non-Dimming, Chicago Plenum Rated			●			6	1	
BG1578100	LC6SLDMCP	785235432092	6" Standard Lumen LED Housing, 120V-277V Non-Dimming, Chicago Plenum Rated			●			6	1	
BG1569200	6LCSL10L35K8	785235431606	6" Standard Lumen Commercial LED Light Engine Assembly, 1000 Lumens, 3500 Kelvin, 80 CRI, clear reflector	●	●	●		●	1.72	1	●
BG1569600	6LCSL10L35K8WT	785235431644	6" Standard Lumen Commercial LED Light Engine Assembly 1000 lumens, 3500 Kelvin, 80 CRI, clear reflector and white trim	●				●	1.72	1	●
BG1569500	6LCSL10L40K8WT	785235431637	6" Standard Lumen Commercial LED Light Engine Assembly, 1000 Lumens, 4000 Kelvin, 80 CRI, clear reflector and white trim						1.72	1	●
BG1569300	6LCSL14L35K8	7852354131613	6" Standard Lumen Commercial LED Light Engine Assembly, 1400 Lumens, 3500 Kelvin, 80 CRI, clear reflector	●	●	●		●	1.72	1	●
BG1569900	6LCSL14L35K8WH	785235431675	6" Stanard Lumen Commercial LED Light Engine Assembly, 1400 Lumen, 3500 Kelvin, 80 CRI, white reflector and trim	●				●	1.72	1	
BG1569700	6LCSL14L35K8WT	785235431651	6" Standard Lumen Commercial LED Light Engine Assembly, 1400 Lumens, 3500 Kelvin, 80 CRI, clear reflector and white trim	●				●	1.72	1	●
BG1570100	6LCSL14L40K8	785235431699	6" Standard Lumen Commercial LED Light Engine Assembly, 1400 Lumens, 4000 Kelvin, 80 CRI, clear reflector		●	●			1.72	1	●
BG1569400	6LCSL18L35K8	785235431620	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 4000 Kelvin, 80 CRI, clear reflector	●	●	●		●	1.72	1	●
BG1569800	6LCSL18L35K8WT	785235431668	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 3500 Kelvin, 80 CRI, clear reflector and white trim	●	●	●		●	1.72	1	●
BG1570000	6LCSL18L40K8	785235431682	6" Standard Lumen Commercial LED Light Engine Assembly, 1800 Lumens, 4000 Kelvin, 80 CRI, clear reflector		●	●		●	1.72	1	●
BG1577700	LC6ML	785235432139	6" Medium Lumen LED Housing 120V-277V 0-10V 10% Dimming	●				●	5.58	2	
BG1525900	6LCML24L35K8	785235430982	6" Medium Lumen Commercial LED Light Engine Assembly, 2400 Lumens, 3500 Kelvin, 80 CRI, clear reflector	●					3.77	1	
BG1526000	6LCML30L35K8	785235430999	6" Medium Lumen Commercial LED Light Engine Assembly, 3000 Lumens, 3500 Kelvin, 80 CRI, clear reflector	●	●				3.77	1	
BG1564500	LC6HL	785235431293	6" High Lumen LED Housing 120V-277V 0-10V 5% Dimming	●	●				4.97	2	
BG1564600	LC8HL	785235431309	8" High Lumen LED Housing 120V-277V 0-10V 5% Dimming	●	●				4.97	2	

QS

10

10-Day Quick Ship Ordering Guide

Order Limit Per Fixture Selection: 50 Pieces or Less

All Non Stocked LiteFrame Commercial Housings including 8” are Quick Ship.

QS

5

5-Day Quick Ship Ordering Guide

Order Limit Per Fixture Selection: 20 Pieces or Less

LC6SL	EM	6LCSL	14L	35K	8	WH	EM
HOUSING	HOUSING OPTION	TRIM APERTURE	OUTPUT	KELVIN	CRI	REF. FINISH/ COLOR OPTION	REF. OPTIONS
LC6SL Standard lumen non-dimming 120V-277V	EM Integral Battery Pack	6LCSL Standard Lumen Clear Alzak Reflector	10L ² Nominal 1000 delivered lumens	27K 2700 Kelvin	8 Nominal 80+ CRI	WH Painted white reflector and trim	WT Painted white flange
LC6ML ¹ Medium lumen 0-10V 10% dimming 120V-277V	277 277V	6LCML Medium Lumen Clear Alzak Reflector	14L ² Nominal 1400 delivered lumens	30K 3000 Kelvin			WW Wall Wash
			18L ² Nominal 1800 delivered lumens	35K 3500 Kelvin			EM Integral Battery with pre-punched reflector
			24L ³ Nominal 2400 delivered lumens	40K 4000 Kelvin			
			30L ³ Nominal 3000 delivered lumens				
						¹ Not available with EM option	
						² 10L, 14L and 18L for use with SL housing type	
						³ 24L and 30L for use with ML housing type	



LiteBox® Plus Housing and Trims

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1565800	LBP6	785235431316	6" LiteBox Plus+ LED Housing	●	●	●	●	●	4.20	1	●
BG1569000	6LBP8L30KWH	785235431361	6" White trim, 800 Lumen 120-277 dual 1% dimming, 3000K	●			●		2.55	1	●
BG1569100	6LBP8L35KWH	785235431378	6" White trim, 800 Lumen 120-277 dual 1% dimming, 3500K	●			●		2.55	1	●
BG1565900	6LBP11L30KWH	785235431323	6" White trim, 1100 Lumen 120-277 dual 1% dimming, 3000K	●		●	●		2.55	1	●
BG1566000	6LBP11L35KWH	785235431330	6" White trim, 1100 Lumen 120-277 dual 1% dimming, 3500K	●			●		2.55	1	●
BG1566100	6LBP15L30KWH	785235431347	6" White trim, 1500 Lumen 120-277 dual 1% dimming, 3000K	●		●	●		2.55	1	●
BG1566200	6LBP15L35KWH	785235431354	6" White trim, 1500 Lumen 120-277 dual 1% dimming, 3500K	●			●		2.55	1	●
BG1579400	LBP6CP	785235432252	6" CP Rated LiteBox Plus+ LED Housing			●			4.20	1	●



LiteBox® 6" LED Surface Downlight New & Retrofit Applications

- 17 watt input power, 1032 lumens
• Installs to standard 4x4 J-Box
- ENERGY STAR® Qualified
• California Title 24 compliant
- Wet Listed

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1505100	LBSLEDA10L30K9 WH	785235430128	Surface Mount LED Module 1000 lumens, 3000 Kelvin, 90 CRI	●	●	●	●	●	1.4	8	●
BG1521300	LBSQLEDA10L30K9 WH	785235430869	Square Surface Mount LED Module 1000 lumens, 3000 Kelvin, 90 CRI	●				●	1.4	8	●
BG1535600	LBSMTGKIT	785235431064	Mounting Kit for LiteBox LED Surface fixtures	●					0.4	8	



LiteBox® 6" and Line Voltage IC/Non-IC Housings & Trims

- Ideal for residential and multi-family applications
• AirShield/AirTight
• Dual rated for IC and Non-IC rated applications
- Pro-Nail™ Bar Hanger
• Patented single torsion spring trim

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1443000	DBX	785235429030	6" housing, line voltage, for new construction. Dual labeled for IC/ non-IC.	●	●	●	●	●	4.2	8
BG1443100	DBXQC	785235428972	6" housing, line voltage, for new construction. Dual labeled for IC/ non-IC, quick connect.	●	●	●		●	4.2	8
BG233700	RMNCD	785235514309	6" housing, line voltage remodel, Dual labeled for IC/ non-IC.	●					3.3	6
BG233800	TA60	785235514316	6" White eyeball	●					0.7	6
BG234100	TAW65	785235514323	6" White regressed eyeball	●					0.9	6
BG234200	TB60	785235514330	Stepped black baffle			●			1.2	12
BG234300	TBW60	785235514347	6" Stepped white baffle	●	●	●	●		0.2	12
BG234500	TBW61	785235514354	6" Long-neck white baffle	●	●	●	●	●	0.2	12
BG234800	TL60	785235514385	6" Drop Opal shower. non-metallic flange. Wet location listed.		●				1.7	6
BG235000	TL62	785235514408	6" Fresnel shower. non-metallic flange. Wet location listed.			●			0.8	6
BG235100	TL63	785235514415	6" Domed polycarbonate shower. Wet location listed.			●			0.5	6
BG235200	TL64	785235514422	6" White Albalite flush glass shower. Wet location listed.	●	●				0.5	6
BG235600	TO6	785235517188	6" White cone	●		●			0.2	12
BG235700	TO60C	785235514460	6" Clear anodized reflector	●	●				0.2	12
BG236000	TO61	785235514477	6" White open splay			●		●	0.2	12



LiteBox® 6" LED Downlight New & Retrofit Applications

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1443200	DBXQL	785235428989	6" housing, QuickLink LED, for new construction. Dual labeled for IC/ non-IC.	●	●	●	●	●	4.9	8	
BG1563400	DBXQL CP	785235431422	6" Chicago Plenum housing, line voltage, for new construction. Dual labeled for IC/non-IC			●			5.0	8	
BG1477800	LB6LEDA10L30K WH	785235429337	6" White trim, 120V w/ dimming to 15% 1000 Lumen 3000K		●	●	●	●	1.5	8	●
BG1477900	LB6LEDA10L35K WH	785235429344	6" White trim, 120V w/ dimming to 15% 1000 Lumen 3500K		●	●	●	●	1.5	8	●



LiteBox® 5" LED Surface Downlight New & Retrofit Applications

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1529200	LBS5LEDA6L30K9 WH	785235430944	Surface Mount LED Module 1000 lumens, 3000 Kelvin, 90 CRI, j-box mount	●	●			●	0.91	8	●



LiteBox® 6" Compact Fluorescent IC/AirShield™ Rated Downlights and Trims

- Residential and light commercial new construction applications
 - Patented single torsion spring trim
- Full reflector design eliminates light leaks
 - UL/CUL listed for damp locations
 - Pro-Nail™ Bar Hangers come standard


Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1443600	IBX26ICAT	785235429023	6" housing, 26W CFL, IC/AirShield	●		●			7	8
BG234200	TB60	785235514330	Stepped black baffle			●			1.2	12
BG234300	TBW60	785235514347	6" Stepped white baffle	●	●	●	●		0.2	12
BG234500	TBW61	785235514354	6" Long-neck white baffle	●	●	●	●	●	0.2	12
BG234800	TL60	785235514385	6" Drop Opal shower. non-metallic flange. Wet location listed.		●				1.7	6
BG235100	TL63	785235514415	6" Domed polycarbonate shower. Wet location listed.			●			0.5	6
BG235200	TL64	785235514422	6" White Albalite flush glass shower. Wet location listed.	●	●				0.5	6
BG235600	TO6	785235517188	6" White cone	●		●			0.2	12
BG235700	TO60C	785235514460	6" Clear anodized reflector	●	●				0.2	12
BG236000	TO61	785235514477	6" White open splay			●		●	0.2	12



LiteBox® 4" Line Voltage IC/Non-IC Housings and Trims

- Small, concealed line-voltage source
 - Pro-Nail™ Bar Hanger
 - Designed for accent lighting of residential and light commercial applications
- AirShield/AirTight
 - Lamp aiming of 360° horizontally and 20° vertically

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG977600	BX4-120	785235043618	4" housing, line voltage, non-IC rated, for new construction.	●		●			4.9	6
BG1475100	IBX4-120	785235430722	4" housing, line voltage, IC rated, for new construction. AirShield™ rated	●	●				6.7	4
BG202900	RMN4-120	785235182355	4" housing, line voltage, non-IC remodel		●	●	●		0.8	6
BG203100	TA120WBF	785235182133	4" White baffle	●					0.4	6
BG203200	TA120BF	785235182140	4" Black baffle	●					0.4	6
BG203400	TA120C	785235182164	4" Clear anodized reflector	●					0.4	6



LiteBox® 6" Housings for 9° to 45° Sloped Ceilings and Trims

- Designed for sloped or “cathedral” type ceilings installations with slopes 0° to 45°
 - Pro-Nail™ Bar Hanger
- AirShield/AirTight
 - IC-rated for direct contact with insulation
 - Damp Listed

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG977700	SCIBX	785235043625	6" housing, 45° sloped ceiling line voltage, IC rated, for new construction.	●					5	1
BG204100	TSC6WBF	785235182232	6" White baffle	●					1	6



LiteBox® 6" Line Voltage IC Rated Shallow Plenum Housing

- UL/CUL listed and approved for use in damp locations
 - AirShield/AirTight
- Accommodates ceilings up to 1-1/2” thick
 - Pro-Nail™ Bar Hanger

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1467000	IBXS	785235429221	6" housing, line voltage shallow plenum, IC rated, remodel			●	●		4.12	6



LiteBox® 4" Low Voltage IC and Non-IC Trims

- CSA Listed
 - IC Rated and Non IC Rated Trims
- Wet Listed
 - Pro-Nail Bar Hangers

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG202100	TA12WBF	785235182034	4" White baffle	●					0.4	6
BG202200	TA12BF	785235182041	4" Black baffle	●					0.4	6
BG202300	TA12C	785235182058	4" Clear anodized reflector	●					0.4	6



LiteBox® Accessories

- Designed to work with 8” or 10” wood joist ceilings at 16” or 24” centers
 - Product is shipped in 8-pack cartons and must be ordered in multiples of 8
- ICBOX can be used with the following Prescolite LiteBox Non-IC housings: BX4-120, BX4-12, TBX, FT6, FT6CF

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG939700	ICBOX	785235041355	Recessed Enclosure for non-IC housings in IC applications		●				1	1



LiteBox® LB4/LBEB4 - 4" Recessed Downlight

- Corresponding fixed and directional downlights
 - For new and existing construction
- Designed for accent lighting of residential and light commercial applications
 - Suitable for wet locations

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1576000	LB4A6L27K9 WH	785235431828	4" Downlight, 600 Lumen, 2700K 9W LED, 120V with 10% dimming, White Trim			●			0.60	1
BG1573600	LB4A6L30K9 WH	785235431705	4" Downlight, 600 Lumen, 3000K 9W LED, 120V with 10% dimming, White Trim			●			0.60	1
BG1573700	LB4A6L35K9 WH	785235431712	4" Downlight, 600 Lumen, 3500K 9W LED, 120V with 10% dimming, White Trim			●			0.60	1
BG1573800	LB4A6L40K9 WH	785235431729	4" Downlight, 600 Lumen, 4000K 9W LED, 120V with 10% dimming, White Trim			●			0.60	1
BG1576200	LBEB4A6L27K9 WH	785235431903	4" Eyeball Downlight, 600 Lumen, 2700K 9W LED, 120V with 10% dimming, White Trim, Eyeball			●			1.05	1
BG1574200	LBEB4A6L30K9 WH	785235431767	4" Eyeball Downlight, 600 Lumen, 3000K 9W LED, 120V with 10% dimming, White Trim, Eyeball			●			1.05	1
BG1574300	LBEB4A6L35K9 WH	785235431774	4" Eyeball Downlight, 600 Lumen, 3500K 9W LED, 120V with 10% dimming, White Trim, Eyeball			●			1.05	1



LiteBox® LB6/LBEB6 - 6" Recessed Downlight

- Corresponding fixed and directional downlights
 - For new and existing construction
- Designed for accent lighting of residential and light commercial applications
 - Suitable for wet locations

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1576100	LB6A7L27K9 WH	785235431866	6" Downlight, 700 Lumen, 2700K 10W LED, 120V with 10% dimming, White Trim			●			1.05	1
BG1573900	LB6A7L30K9 WH	785235431736	6" Downlight, 700 Lumen, 3000K 10W LED, 120V with 10% dimming, White Trim			●			1.05	1
BG1574000	LB6A7L35K9 WH	785235431743	6" Downlight, 700 Lumen, 3500K 10W LED, 120V with 10% dimming, White Trim			●			1.05	1
BG1574100	LB6A7L40K9 WH	785235431750	6" Downlight, 700 Lumen, 4000K 10W LED, 120V w/ 10% dimming, White Trim			●			1.05	1
BG1576300	LBEB6A7L27K9 WH	785235431941	6" Eyeball Downlight, 700 Lumen, 2700K 10W LED, 120V with 10% dimming, White Trim, Eyeball			●			2.00	1
BG1574500	LBEB6A7L30K9 WH	785235431798	6" Eyeball Downlight, 700 Lumen, 3000K 10W LED, 120V with 10% dimming, White Trim, Eyeball			●			2.00	1
BG1574600	LBEB6A7L35K9 WH	785235431804	6" Eyeball Downlight, 700 Lumen, 3500K 10W LED, 120V with 10% dimming, White Trim, Eyeball			●			2.00	1



10-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 50 Pieces or Less

LBC6	W	WH
HOUSING	MOUNTING	FINISH OPTIONS
LBC6 6" cylinder housing	W Wall Mount, Down P Pendant Mount S Surface Mount CM Cord Mount	WH White BL Black Z Zet BA Brushed Aluminum BZ Bronze



Downlight Accessories

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
AE101000	B6	785235208567	Set of two bar hangers for ceiling joists up to 24" centers	●	●	●	●	●	0.9	1
BE767500	B24	785235103633	Set of two 24" bar hangers for T-bar ceilings	●	●	●	●	●	1.6	1
SA201000	FSDFI	785235514712	Fuse kit for field installation			●			1	1



FireTight™ 6" Fire-Resistant Housing and LED Trims

- AirShield/AirTight
 - Energy saving LED light engine
- One and two hour fire ratings available
 - ENERGY STAR® Qualified

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton	Energy Star
BG1332000	FT6QLIC	785235429177	6" housing, FireTight LED, IC rated for QuickLink	●		●					
BG1477800	LB6LEDA10L30K WH	785235429337	6" White trim, 120V w/ dimming to 15% 1000 Lumen 3000K		●	●	●	●	1.5	8	●
BG1477900	LB6LEDA10L35K WH	785235429344	6" White trim, 120V w/ dimming to 15% 1000 Lumen 3500K		●	●	●	●	1.5	8	●



FireTight™ 6" Fire-Resistant Housings and Trims

- One and two hour fire ratings available
 - Non-IC rated, new construction
- AirShield/AirTight
 - Damp Listed
- Includes hardware for mounting to furring channels

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG590700	FT6	785235301527	6" housing, FireTight Incandescent Line Voltage non-IC rated	●					11	1
BG233800	TA60	785235514316	6" White eyeball	●					0.7	6
BG234100	TAW65	785235514323	6" White regressed eyeball	●					0.9	6
BG234200	TB60	785235514330	Stepped black baffle			●			1.2	12
BG234300	TBW60	785235514347	6" Stepped white baffle	●	●	●	●		0.2	12
BG234500	TBW61	785235514354	6" Long-neck white baffle	●	●	●	●	●	0.2	12
BG234800	TL60	785235514385	6" Drop Opal shower trim. non-metallic flange. Wet location listed.		●				1.7	6
BG235000	TL62	785235514408	6" Fresnel shower trim. non-metallic flange. Wet location listed.			●			0.8	6
BG235100	TL63	785235514415	6" Domed polycarbonate shower trim. Wet location listed.			●			0.5	6
BG235200	TL64	785235514422	6" White albalite flush glass shower trim. Wet location listed.	●	●				0.5	6
BG235600	TO6	785235517188	6" White cone	●		●			0.2	12
BG235700	TO60C	785235514460	6" Clear anodized reflector	●	●				0.2	12
BG236000	TO61	785235514477	6" White open splay			●		●	0.2	12
BE120201	TL42	785235161800	6" Fresnel glass with reflector 60W A-19	●					1.4	6



QS710 10-Day Quick Ship Ordering Guide
Order Limit Per Fixture Selection: 50 Pieces or Less

ORDERING INFORMATION

SLLED

HOUSING

SLLED1 High output 13W LED step light

SLLED2 Recessed 13W LED step light

SLLED3 Residential 9W LED step light

SLLED135KBL

35K

LED COLOR TEMP

35K 3500 Kelvin

50K 5000 Kelvin

BL

HOUSING FINISH

WH White

BL Black

Z Zet (Metallic Silver)

BZ Bronze

HOUSING OPTION

Blank 120V

277 277V

HOUSING ACCESSORIES

SLMB Dry wall bar hanger installation kit

SLD12CMB Concrete mounting box SLLED1 and SLLED2

SLD3CMB Concrete mounting box SLLED3

ORDERING INFORMATION

MSL

HOUSING

MSL Mini Step Light

EXAMPLE: MSLHL30K8 WH

HL

COVER PLATE

HL Horizontal Louver

VL Vertical Louver

HH Horizontal Hood

VH Vertical Hood

30K

LED COLOR

30K 3000 Kelvin

40K 4000 Kelvin

50K 5000 Kelvin

8

CRI

8 80 CRI

WH

FINISH

WH White

BL Black

BN Brushed Nickel

AB Antique Bronze



CDL- 4", 5" or 6" Recessed Downlight

- Wet Listed
 - UL Listed
- Dimming range from 100% - 10%
 - Highly reflective matte white finish

Part Number	Catalog Number	UPC Code	Description	CA 03	GA 27	IL 06	NJ 12	TX 04	Wt. each	# on Carton
BG1576800	CDL4-7L30KAWH	785235432047	4" Downlight, 700 Lumen, 3000K, 120V, 90 CRI, White Trim		●	●			0.52	1
BG1576900	CDL6-8L30KAWH	785235432054	6" Downlight, 800 Lumen, 3000K, 120V, 90 CRI, White Trim		●	●			0.96	1

All ArchiTrak products are stocked except the following:

Catalog Number	Description
AKTMNLED	2" 14W Track Mounted LED 120V
AKTMDLED	2" 24W Track Mounted LED 120V
AKTMLLED	4" 45W Track Mounted LED 120V
AKTCLS	Current Limiter Device



QS710

10-Day Quick Ship Ordering Guide

Order Limit Per Fixture Selection: 50 Pieces or Less

ORDERING INFORMATION					
EXAMPLE: AKTMLED25L35K8XFL55BL					
AKTMLED	25L	35K	8	XFL55	BL
FIXTURE	OUTPUT	COLOR	CRI	BEAM SPREAD	FINISH
AKTMLED	25L 2500 Deliv-ered Lumens	27K 2700 Kelvin 30K 3000 Kelvin 35K 3500 Kelvin 40K 4000 Kelvin	8 80+ CRI 9 90+ CRI	MD25 25 Degree Cutoff FL35 35 Degree Cutoff XFL55 55 Degree Cutoff	BL Black WH White

LiteForms®



QS710

10-Day Quick Ship Ordering Guide

Order Limit Per Fixture Selection: 50 Pieces or Less

ORDERING INFORMATION									
EXAMPLE: LCC6LEDP18L35K8WFL45 BL									
LCC6LED	P	18L	35K	8			WFL45		BL
HOUSING	LED COLOR TEMP		CRI	OPTIONS		BEAM	REFLECTOR FINISH	CYLINDER COLOR	
LCC6LED 6" LED Cylinder	27K	2700 Kelvin	8 80+ CRI	Blank	Standard 0-10V dimming to 10%	WFL45 Nominal 45 Degree Cutoff	Blank Clear Alzak, Semi-Dif-fuse	BA	Brushed Aluminum
MOUNTING	30K	3000 Kelvin	VOLTAGE					BZ	Bronze
	35K	3500 Kelvin	Blank	120V-277V				BL	Matte Black
	40K	4000 Kelvin	120V	120 Volt (for 2DM)				WH	Matte White
	50K	5000 Kelvin						Z	Zet
OUTPUT		NOTES							
10L	1000 Delivered Lumens	¹ Cord length 6 feet, clear sleeve ² Plastic bushings are grey on white, brushed aluminum and zet cylinder; black on black and bronze							
14L	1400 Delivered Lumens								
18L	1800 Delivered Lumens								
P	Pendant								
S	Surface								
CM ^{1,2}	Cord Mount								
W	Wall Mount								

