Product data sheet
Characteristics

HVL315BW
Switchgear, HVL, single, 600A, 15kV, 3 pole, 10E to 400E boric acid fuse, NEMA 3R



Main

Product	Switched fuse mechanism
Included Accessory	Enclosure heater
Not Included	Fuse to be ordered separately

Complementary

Protection type	Fuse boric acid
Associated fuse rating	10 A E 15 A E 20 A E 25 A E 30 A E 40 A E 50 A E 65 A E 80 A E 100 A E 125 A E 150 A E 175 A E 200 A E 250 A E 300 A E 400 A E
Line Rated Current	600 A
Momentary Amperes Asymmetrical	40 kA
Frequency	50/60 Hz
Number of Poles	3P
Highest voltage for equipment (Um)	15 kV
Basic Inulation Level	90 kV
Enclosure Rating	NEMA 3R
Electrical Connection	Lugs
Type of Installation	Outdoor
Wire Gauge	AWG 2...600 kcmil aluminium/copper
Enclosure Width	38 in (965.20 mm)
Enclosure Depth	60 in (1524.00 mm)
Enclosure Height	97 in (2463.80 mm)

Environment

Product Certifications	cUL[RETURN]UL Listed

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	US1PE5A07945
Discount Schedule	PE5A
GTIN	785901741503
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1400.0004 lb(US) (635.029 kg)

Contractual warranty

Warranty	18 months