Transformer (TC152-12TP) Specification Sheet

Project Name:	Location:	MFG: Philips Hadco
Fixture Type:	Catalog No.:	Qty:



Ordering Guide

Example: TC152-12TP

Product Code	TC152-12TP Transformer

Specifications

HOUSING:
Housing and cover are polyester powdercoated steel with removable door. Internal transformer is epoxy encapsulated. Exterior Mounting - Transformer should be mounted on the wall, structure, or post in the vertical position. Cable entries should be positioned downward.

ELECTRICAL ASSEMBLY:
The transformer is thermally protected and is shielded between the 120V input and the low voltage output, for safety. Insulation type transformers for safe operation. 6-ft heavy-duty 18-3 AWG, 105° C, SJT power cord with 3 prong grounded wall plug. Voltage control switch: Low = 11.5V, High = 12.5V. Euro-Board terminal block for easy low voltage cable attachment. Line voltage amperage draw: 150VA = .9AMP. Includes integral timer and photocell. 50/60Hz input. Consult factory for details.

CERTIFICATIONS:
ETL Listed to U.S. safety standards for wet locations. cETL listed to Canadian safety standards for wet locations. Manufactured to ISO 9001:2008 Standards.

WARRANTY:
Ten-year limited warranty.

Height :
11 1/4" (286mm)

Width:
3 1/2" (89mm)

Depth:
3 3/4" (95mm)

Note: Philips reserves the right to modify the above details to reflect changes in the cost of materials and/or production and/or design without prior notice.
100 Craftway Drive, Littlestown, PA 17340 | P: +1-717-359-7131 F: +1-717-359-9289 | http://www.hadco.com | Copyright 2013 Philips
HW2