GE Lighting

10490 - F40/30BX/SPX50RS

GE Biax® T5 - Facilities; Retail Display; Hospitality; Office; Restaurant; Warehouse

High Color Rendering
Energy Savings







GENERAL CHARACTERISTICS

Lamp Type	Compact Fluorescent - Plug-In
Bulb	T5
Base	4-Pin (2G11)
Equivalent Wattage	180.0 W
Rated Life	20000.0 hrs
Starting Temperature (MIN)	10.0 °C
LEED-EB MR Credit	74 picograms Hg per mean lumen hour
Primary Application	Standard;Facilities;Retail Display;Hospitality;Office;Restaurant;Wa

PHOTOMETRIC CHARACTERISTICS

Initial Lumens	2900.0
Mean Lumens	2700.0
Nominal Initial Lumens per Watt	72
Color Temperature	5000.0 K
Color Rendering Index (CRI)	80.0

ELECTRICAL CHARACTERISTICS

Wattage	40.0
Voltage	126.0
Lamp Current	0.32 A
Current Crest Factor (MAX)	1.7

DIMENSIONS

Maximum Overall Length (MOL)	22.5000 in(571.5 mm)
Nominal Length	22.500 in(571.5 mm)

PRODUCT INFORMATION

Product Code	10490
Description	F40/30BX/SPX50RS
ANSI Code	60901-IEC-6240-2
Standard Package	Case
Standard Package GTIN	10043168104903
Standard Package Quantity	36
Sales Unit	Unit
No Of Items Per Sales Unit	1
No Of Items Per Standard Package	36
UPC	043168104906

CAUTIONS & WARNINGS

Caution

• Lamp may shatter and cause injury if broken
  - Remove and install by grasping only plastic portion of the lamp.

NOTES

• 4-Pin lamp minimum starting temperature is a function of the ballast. Most ballasts are rated with a minimum starting temperature of 50 degrees F (10 C). Ballasts are also available that provide reliable starting to 0 degrees F (-18C) and -20 F (-29C).

• Based on 60Hz reference circuit.

• Fluorescent lamp lumens decline during life

• Life ratings based on rapid start operation. On instant start ballast, life rating is 25% lower.