Rittal – The System.

Faster – better – everywhere.

Ex Enclosures Stainless steel, empty enclosure with screw fastened cover – KE 9302.000

Date : May 24, 2018

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

Ex Enclosures Stainless steel, empty enclosure with screw fastened cover – KE 9302.000

created: 24.05.2018 build on www.rittal.com/us-en



Product description

Applications:	Zone 1 and 2 or 21 and 22 to 94/9/EC Ambient temperature range: -30°C...+80°C The specified temperatures can be limited by the installed equipment Protection type to EN 60 079: Equipment protection due to increased safety, equipment protection due to enclosure
Material:	Housing: Stainless steel 1.4301 (AISI 304) Cover: Stainless steel 1.4301 (AISI 304), all-round foamed-in silicone seal
Surface finish:	Housing: Brushed, grain 240
Protection category IP to IEC 60 529:	IP 66
Certificates:	IEC Ex PTB 09.0033U: yes PTB 03 ATEX 1013U: yes
Supply includes:	Housing Cover
Base material:	Stainless steel

Product features

Dimensions:	Height: 150 mm (5.9 ″) Width: 300 mm (12 ″) Depth: 80 mm (3.1 ″)
Packaging unit:	1 pc(s).

© Rittal 2018

Weight/packaging unit:	1.8 kg (4 lb.)
EAN:	4028177138568
Customs tariff number:	94032080
ETIM 6.0:	EC002503
ETIM 5.0:	EC002503
eCl@ss 8.0/8.1:	27180502
eCl@ss 7.0/7.1:	27180502
eCl@ss 6.0/6.1:	27180502
eCl@ss 5.1/5.1.4:	27180502
Product description (long):	KEL Ex enclosure, WHD: 300x150x80 mm, Stainless steel 1.4301, without mounting plate, Empty enclosure with screw-fastened cover

Approvals

Approvals:	ATEX IEC Ex
Certificates:	EAC Ex
Declarations:	Manufacturer's declaration

© Rittal 2018