Product data sheet

Specifications



Active harmonic filter 200 amp 380-480 VAC N2 Enclosure [TAA]

PCSP200D5N2

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Range of Product	AccuSine
Product name	AccuSine PCS+
Product or Component Type	Active harmonic filter

Complementary

Network type	3P
Network configuration	3 or 4 wires
Network rated voltage	380…480 V AC
Input Frequency	50/60 Hz +/- 3 Hz auto sensing
Maximum permissible voltage	1.1 x Un
Neutral correction	Not provided
RMS output current rating	200 A
Reactive power rating	166 kvar 480 V AC 50/60 Hz
Operating modes	Power factor correction Harmonic cancellation Mains current balancing
Installation location	Indoor
Enclosure mounting	Floor-standing
Protection Type	Circuit breaker protection
Disconnect type	Door-interlocked with rotary handle
Interrupt capacity	200 kA
Heat dissipation	Rear plenum with forced ventilation for high heat flow
Electromagnetic compatibility	Conducted EMC, class A EN 61000-6-4
Accessibility for operation	Front
Location of connection	Top or bottom

Environment

Enclosure degree of protection	UL type 2
Environmental characteristic	Operating 3C2 IEC 60721-3-3 Operating 3S2 IEC 60721-3-3 Storage 3C3 IEC 60721-3-3 Storage 3S3 IEC 60721-3-3
Operating altitude	<= 3280.84 ft (1000 m) 1 % per 100 m
Ambient air temperature for operation	32…104 °F (0…40 °C) 32…122 °F (0…50 °C) maximum with current derating of 2 % per °C

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Relative humidity	0…95 %
PCBA protection	Conformal coated
Standards	CSA C22.2 No 60947-1-07 EN 61000-6-4 UL 508 UL 60947-1 CSA C22.2 No 14 EN 60439-1
Product Certifications	cULus ABS CE RCM
Ambient Air Temperature for Storage	-4…140 °F (-20…60 °C)
Product Weight	782.6 lb(US) (355 kg)
Height	82.7 in (2100 mm)
Width	35.4 in (900 mm)
color	Light gray RAL 7035)
Depth	23.6 in (600 mm)

Ordering and shipping details

Category	US1DE2C00089
Discount Schedule	DE2C
GTIN	3606480851094
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	91.8 in (233.1 cm)
Package 1 Width	47.008 in (119.4 cm)
Package 1 Length	47.008 in (119.4 cm)
Package weight(Lbs)	1047.2 lb(US) (475.0 kg)

Compliance

Compliance	TAA Compliant BAA Compliant via COTS

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**162 ton CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**3 825 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**349 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**121 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**157 ton CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**659 kg CO2 eq.**
Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**41f8a5bd-7758-4f6b-8e3f-271055f150ec**
EU RoHS Directive	Compliant By Exemption
REACh Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Longer

Lifetime extension

Repair	**No**

Use Again

Repack and remanufacture

Recyclability potential, in %	**72**
Circularity Profile	End of Life Information
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.**

Technical Illustration

Assembly's dimensions

