HUBBELL
Wiring Device-Kellems

Hubbell-Pro Residential AUTOGUARD® Self-Test GFCI Receptacle, 15A, Light Almond

By Hubbell Wiring Device-Kellems
Catalog # GF15LA

HUBBELLPRO, GFCI, 15A, Light Almond



Features

- Ground fault EOL indicator
- Comprehensive diagnostics
- No power at face if reverse wired
- Automatic self-grounding staple makes installation ease

Application

Heavy Duty Commercial Grade

Performance

Electrical - Amperage - 15A/20A, 20A Feed Thru, Electrical - Max. Interrupting Capacity - 10,000A, Electrical - Voltage - 120V AC +10% - 15% (102V to 132V), Environmental - Maximum Humidity - 0.95, Environmental - Operating Temperature - -35°C to 66°C or -30°F to 150°F.

Specifications

Environmental Conditions	Indoor Dry Unless Protected By Additional Means
EU RoHS Indicator	Yes
Industry Standard(s)	Meets UL498 For Receptacles
Nema Rating	5-15R

Conductor

Number Of Wires	3-Wire Grounding
Wire Size	#14 AWG to #12 AWG
Number Of Poles	2-Pole

Current

Current Rating	15 A
Voltage Rating Description	125 VAC
Phase	Single Phase
Current / Amperage Rating	15 A
Connectivity	Back and Side Wired Screw Terminals
Wattage	1875
Voltage Rating	125 VAC

Dimensions

Display Size	Standard Sized Product

General

OEM Brand Name	Hubbell Wiring Device-Kellems
Color	Light Almond
Item Type	Decorator Duplex
Material - Mounting Hardware	Screw Mounting
Type	Standard
Material	Thermoplastic
Specifications	• Codes - Meets all NEC® and CEC requirements • Frequency - 60 Hz • Trip Level - 4 to 6 mA • Trip Time - .025 second nominal
UPC	883778450563

Logistics

Carton Quantity	10
Pallet Quantity	1200

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [English]

© 2026 Hubbell Incorporated. All rights reserved