BRYANT®

FSP Adapter Panel, 6-Fiber, SC/APC Simplex, 6-Port, Loaded with 6 Adapters, Zircon Sleeves, Green



By Bryant
Catalog # FSPSCA6

FSP Adapter Panel, 6-Fiber, SC/APC Simplex, 6-Port, Loaded with 6 Adapters, Zircon Sleeves, Green

Features

-
-
-

Application

Interconnect

Performance

- Electrical - SM/MM insertion loss - Less than 0.50dB (0.25dB typical)
- Environmental - Operating temperature - 0 ºC to +75 ºC

General

Adapter Type	SC Simplex, APC
Catalog Number	FSPSCA6
Color	Green
EU RoHS Indicator	Yes
Enclosure Type	Various
Environmental Conditions	Indoor
Item Type	6) SC Simplex
Material	Ceramic Zirconium
Material - Mounting Hardware	Snap-In
Number Of Ports	6
Repeatability	0.1 dB
Service Life	500 matings
Single/Multimode	SM
Specifications	• Dimensions - 1.1” W X 5.1” H • Finish - Durable black powder coat • Material - 16ga cold rolled steel • Sleeve Material - Zirconia Ceramic
Temperature Rating	-40C to +85C
UPC	662620829593

Dimensions

Display Size	5.1" X 1.1"

Electrical Ratings

Connectivity	Receptacle
Insertion Loss	0.30 dB
Return Loss	55

Conductor Related

Fiber Size	125 Micron
Fiber Type	Singlemode

Certifications And Compliance

Industry Standard(s)	• TIA-568-C.3 • TIA-604-FOCIS

Logistics

Carton Quantity	4

Product Assets

Specifications - FSPSCA6

©2025 Hubbell Incorporated. All rights reserved