Product data sheet
Characteristics

QMB366MW
SWITCH, FUSIBLE QMB 600V 600A 3P MAIN



Main

Product or Component Type	Fuse-switch
Device Application	Main supply
Range of Product	Square D QMB

Complementary

Line Rated Current	600 A
Material	Steel
Number of poles	3
Rated Voltage	600 V AC
Device mounting	Surface
Product destination	Meter board Distribution board
Protection Type	Fuse protection
Short-circuit protection	100000 A AIR
Switch Function	TPST
Wiring configuration	Without neutral
Standards	NEMA KS1

Environment

Product Certifications	UL Listed

Ordering and shipping details

Category	00037-QMB BRANCH CB,SW,& MAIN SW
Discount Schedule	PE1A
GTIN	785901767060
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	112.00 lb(US) (50.802 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months