Product data sheet
Characteristics

HU362EI
Safety switch, heavy duty, non fusible, 60A, 3 poles, 60 hp, 600 VAC/DC, interlock kit



Main

Product	Single Throw Safety Switch
Current Rating	60 A
Number of Poles	3
Voltage Rating	600 V AC/DC
Wire Size	AWG 14...AWG 3 copper AWG 12...AWG 3 aluminium
Disconnect Type	Non-fusible disconnect
Mounting Type	Surface
Factory Installed Neutral	None
Duty Rating	Heavy duty
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel

Complementary

Short-circuit withstand	200 kA
Maximum Horse Power Rating	10 Hp 240 V AC 50...60 Hz 1 phase NEC 430.52 20 Hp at 240 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 25 Hp 480 V AC 50...60 Hz 1 phase NEC 430.52 50 Hp at 480 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 30 Hp 600 V AC 50...60 Hz 1 phase NEC 430.52 60 Hp at 600 V AC 50...60 Hz for 3 phases motors conforming to NEC 430.52 10 Hp 250 V DC NEC 430.52 30 hp 600 V DC
Width	10.5 in (266.70 mm)
Height	21.25 in (539.75 mm)
Maximum Depth	6.38 in (162.05 mm)
Tightening torque	5.65 N.M (AWG 3) 45 Lbf.In (5.08 N.m) AWG 6...AWG 4) 40 Lbf.In (4.52 N.m) 0.01 in² (8.367 mm²) AWG 8) 50 lbf.in (5.65 N.m) 0.00…0.01 in² (2.06…5.261 mm²) AWG 14...AWG 10)

Ordering and shipping details

Category	00008 - H&HU SW,2&3P,N1,30-200A
Discount Schedule	DE1
GTIN	00785901156550
Nbr. of units in pkg.	1
Package weight(Lbs)	16 lb(US) (7.26 kg)
Returnability	Yes
Country of origin	US

Packing Units

Package 1 Height	7.40 in (18.796 cm)
Package 1 width	10.80 in (27.432 cm)
Package 1 Length	19.80 in (50.292 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
PVC free	Yes

Contractual warranty

Warranty	18 months