Product data sheet
Characteristics

2512MBG1
Two Speed Manual Starter - NEMA 1 - Buttons - 3P - Size M0 - 600VAC

Product availability : Stock - Normally stocked in distribution facility

Price* : 1013.71 USD



Main

Product or component type	Manual Starter
Range of product	M
NEMA size	M-0

Complementary

Auxiliary contact composition	Without
Local signalling	No indicator
Motor power hp	2 hp 200...230 V AC 3 phases 3 hp 380...575 V AC 3 phases
System Voltage	600 V AC
Poles description	3P
Control type	Push-button
Motor starter type	2 speed
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy
Number of thermal units required	3

Environment

Product certifications	CSA UL listed
NEMA degree of protection	NEMA 1 painted sheet steel

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901805021

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Nbr. of units in pkg.	1
Package weight(Lbs)	10.9
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months