

Product data sheet

Specifications



Terminal block, Linergy, fuse holder, Class R, 60A, 600 V, 3 pole

9080FB3621R

Product availability: Stock - Normally stocked in distribution facility

Main

Range	9080FB
Product	Fuse holder

Complementary

Current Rating	60 A
[Ue] rated operational voltage	<= 600 V AC/DC
Fuse type	R
Fuse size	1.0625 x 5.5 in
Number of poles	3
Electrical Connection	Box lugs
Wire Gauge	AWG 14...AWG 2 copper or aluminium
SCCR	200 kA UL 512
Product Certifications	UL listed file E40747 CCN IZLT CE CSA file 70360 class 6225 01
Operating Temperature	-40...302 °F (-40...150 °C)
Mounting Type	Surface mount
Block Material	Phenolic: block
Wire stripping length	0.5625 in (14.2875 mm)
Terminal Tightening Torque	lugs 50 lbf.in (5.6 N.m) AWG 3...AWG 2 copper or aluminium lugs 45 lbf.in (5.08 N.m) AWG 6...AWG 4 copper or aluminium lugs 40 lbf.in (4.5 N.m) AWG 8 copper or aluminium lugs 35 lbf.in (4.0 N.m) AWG 12...AWG10 copper or aluminium lugs 35 lbf.in (4.0 N.m) AWG 14 copper
Height	6.75 in (171.45 mm)
Width	5.08 in (129.03 mm)
Depth	2.12 in (53.85 mm)

Ordering and shipping details

Category	US10CP121701
Discount Schedule	0CP1
GTIN	785901097259
Returnability	Yes
Country of origin	US

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.100 in (5.334 cm)
Package 1 Width	5.100 in (12.954 cm)
Package 1 Length	6.800 in (17.272 cm)
Package weight(Lbs)	22.400 oz (635.029 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	7.200 in (18.288 cm)
Package 2 Width	11.800 in (29.972 cm)
Package 2 Length	22.50 in (57.15 cm)
Package 2 Weight	29.500 lb(US) (13.381 kg)

Contractual warranty

Warranty (in months)	18
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer

 Lifetime extension	
Repair	No

Use Again

 Repack and remanufacture	
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.