# Product data sheet
## Characteristics

# 2510TCG1
## Manual Starter, integral horsepower, NEMA M1, 600 VAC, 2 pole, 3 HP at 230 VAC, single phase, no indicator, NEMA 1



## Main

| | |
|---|---|
| Product | Manual Starter |
| Type | T |
| NEMA Size | M-1 |

## Complementary

| | |
|---|---|
| Control Unit | Toggle switch |
| Pilot Light | No indicator |
| Horsepower Rating | 2 Hp 115 V AC, 1 phase<br>3 hp 230 V AC, 1 phase |
| Voltage Rating | 600 V AC |
| Number of Poles | 2P |
| Starter Type | Non reversing |
| Electrical Connection | Pressure wire clamp |
| Overload Relay Type | Melting alloy |
| Number of Thermal Units Required | 1 |
| Wire Gauge | AWG 14...AWG 8 copper |
| Auxiliary Contacts | Without |
| Height | 8.63 in (219.20 mm) |
| Width | 5 in (127.00 mm) |
| Maximum Depth | 4.13 in (104.90 mm) |

## Environment

| | |
|---|---|
| Certifications | CSA LR60905 class 3211 05<br>UL listed file E42243 CCN NLRV |
| NEMA Enclosure Rating | NEMA 1 painted sheet steel |

## Ordering and shipping details

| | |
|---|---|
| Category | 21103 - 2510,2511,2512 M,T |
| Discount Schedule | CP1 |
| GTIN | 00785901795711 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1 lb(US) (0.45 kg) |
| Returnability | No |
| Country of origin | MX |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

| | |
|---|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation | REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| PVC free | Yes |

## Contractual warranty

| | |
|---|---|
| Warranty | 18 months |