Product data sheet
Characteristics

8501KUD12P14V53
RELAY 240VAC 10AMP TYPE K +OPTIONS

Product availability : Stock - Normally stocked in distribution facility

Price* : 28.70 USD



Main

Range of product	8501K
Product or component type	Relay
Contacts material	Silver tin oxide
Switch function	DPDT
[Uc] control circuit voltage	24 V DC
Rated power in hp	0.33 hp 120 V 0.5 hp 240 V
Maximum switching voltage	240 V AC
Mounting support	Socket
Ambient air temperature for operation	-40...158 °F
Shape of pin	Spade
Product certifications	CE RoHS CSA UL recognized
Operating time	11 ms pick-up 7 ms drop-out
Local signalling	Green indicator on
Control type	Without
Product compatibility	8501NR82
Relay type	General purpose

Ordering and shipping details

Category	21144 - 8501 KU
Discount Schedule	CP2
GTIN	00785901320906
Nbr. of units in pkg.	1
Package weight(Lbs)	0.19

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Returnability	N
Country of origin	CN

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0702 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months