Product data sheet
Characteristics

2510MCO1
Manual Starter - Open Device - Buttons - 2P - Size M1 - 600VAC

Product availability : Stock - Normally stocked in distribution facility

Price* : 315.30 USD



Main

Product or component type	Manual Starter
Range of product	M
NEMA size	M-1

Complementary

Auxiliary contact composition	Without
Local signalling	No indicator
Motor power hp	2 hp at 115 V AC 1 phase 3 hp at 230 V AC 1 phase
System Voltage	600 V AC
Poles description	2P
Control type	Push-button
Motor starter type	Non reversing
Electrical connection	Pressure wire clamp
Thermal overload type	Melting alloy
Number of thermal units required	1
AWG gauge	AWG 14...AWG 8 (copper)
Height	5.72 in
Width	3.5 in
Depth	4.03 in

Environment

Product certifications	CSA LR60905 class 3211 05 UL listed file E42243 CCN NLRV
NEMA degree of protection	Not rated (open device)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	21103 - 2510,2511,2512 M,T
Discount Schedule	CP1
GTIN	00785901792123
Nbr. of units in pkg.	1
Package weight(Lbs)	2
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be compliant Will not be compliant
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months