# Product data sheet
## Characteristics

# 2510FO3P
## FHP Manual Starter - Open - 1P - Key Operated - Red Indicator - 277VAC

Product availability : Stock - Normally stocked in distribution facility

Price* : 144.40 USD



## Main

| | |
|---|---|
| Product or component type | Single Unit Manual Starter |
| Range of product | F |
| Thermal overload type | Melting alloy |

## Complementary

| | |
|---|---|
| Line Rated Current | 16 A |
| Cable entry | Without |
| Motor power hp | 1 hp at 115 V AC<br>1 hp at 230 V AC<br>1 hp at 277 V AC |
| System Voltage | 277 V AC |
| Poles description | 1P |
| Control type | Key |
| Phase | 1 phase |
| Local signalling | Red indicator |
| Reset | Manual |
| Motor starter type | Non reversing |
| Electrical connection | Screw clamp terminals |
| AWG gauge | AWG 14...AWG 12 (copper) |
| Height | 4.13 in |
| Width | 1.69 in |
| Depth | 2.22 in |

## Environment

| | |
|---|---|
| Product certifications | CE<br>CSA LR25490 class 3211 05<br>UL recognized E42243 CCN NLRV2 |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| NEMA degree of protection | Not rated (open device) |

## Ordering and shipping details

| | |
|---|---|
| Category | 21101 - 2510,2511,2512 F |
| Discount Schedule | CP1 |
| GTIN | 00785901077688 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.35999999999999999 |
| Returnability | N |
| Country of origin | MX |

## Offer Sustainability

| | |
|---|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Will not be compliant<br>Will not be compliant |
| REACh | Reference not containing SVHC above the threshold<br>Reference not containing SVHC above the threshold |

## Contractual warranty

| | |
|---|---|
| Warranty period | 18 months |