Product data sheet
Characteristics

8536SCA2V03A
Non-Reversing Starter Size 1P, 2-Pole, Thermal - Melting Alloy

Product availability : Stock - Normally stocked in distribution facility

Price* : 1202.00 USD



Main

Product or component type	Starter
Range of product	S
Line Rated Current	27 A
Product certifications	CSA NEMA UL listed
Control circuit	Common control circuit
Control type	2 momentary push-buttons (START-STOP)
NEMA degree of protection	NEMA 12 painted sheet steel
Rated power in HP	3 HP 115 V AC 5 HP 230 V AC
Poles description	2P
Phase	1 phase
System Voltage	600 V AC
NEMA size	1P
[Uc] control circuit voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 1

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901237587
Nbr. of units in pkg.	1
Package weight(Lbs)	14.81

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months