Product data sheet
Characteristics

8536SCH3V08
Non-Reversing Starter Size 1, 3-Pole, Thermal - Melting Alloy

Product availability : Stock - Normally stocked in distribution facility

Price* : 761.00 USD



Main

Product or component type	Starter
Range of product	S
Line Rated Current	27 A
Product certifications	CSA NEMA UL listed
Control circuit	Common control circuit
Control type	No control units
NEMA degree of protection	NEMA 3R painted sheet steel
Rated power in HP	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC
Poles description	3P
Phase	3 phases
System Voltage	600 V AC
NEMA size	1
[Uc] control circuit voltage	208 V AC 60 Hz
Motor starter type	Non reversing
Electrical connection	Screw clamp terminals
Thermal overload type	Melting alloy 3

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901824596
Nbr. of units in pkg.	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Package weight(Lbs)	13.960000000000001
Returnability	N
Country of origin	MX

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 3Q2014 Will be compliant on 3Q2014
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months