Product data sheet
Characteristics

8501RSD14M1P14V53
RELAY 240VAC 5AMP TYPE R +OPTIONS

Product availability : Stock - Normally stocked in distribution facility

Price* : 39.00 USD

Main

Range of product	8501R
Product or component type	Miniature Relay
Contacts material	Silver tin oxide
Switch function	4PDT
Control circuit voltage	24 V DC
Rated power in HP	Not rated
Mounting support	Socket
Ambient air temperature for operation	-40...158 °F
Shape of pin	Spade
Product certifications	CE CSA RoHS UL recognized
Operating time	20 ms pick-up 20 ms drop-out
Local signalling	Green indicator on
Control type	Test button
Product compatibility	8501NR45
Relay type	Low voltage

Ordering and shipping details

Category	21143 - 8501 R
Discount Schedule	CP2
GTIN	00785901584063
Nbr. of units in pkg.	1
Package weight(Lbs)	8.0000000000000002E-2
Returnability	Y
Country of origin	CN

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1347 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold

Contractual warranty

Warranty period	18 months