Product data sheet
Characteristics

UK7T
Individual meter socket, ringless socket, horn bypass, 4 jaws no release, OH, UG, 400 A, up to 600 VAC three phase 4W



Main

Product or component type	Meter Socket
Meter socket type	Ringless
Hub type	A-L ACPL closing plate

Complementary

Meter socket rated current	400 A
Number of jaws	7 without jaw release
Bypass type	No bypass
Phase	3 phase
[Ue] rated operational voltage	600 V AC
Enclosure material	Steel
Box number	12R
Electrical connection	Studs
Service feed location	UG OH
Wiring configuration	4-wire
Device mounting	Surface
Maximum Depth	6.00 in (152.40 mm)
Maximum Width	20.25 in (514.35 mm)
Maximum Height	43.00 in (1092.20 mm)

Environment

Product certifications	UL Listed
Enclosure Rating	NEMA 3R

Ordering and shipping details

Category	00039 - METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	00785901119746
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	US

Offer Sustainability

EU RoHS Directive	Under investigation

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months