# Product data sheet

Specifications



## Illuminated push-button head, Harmony 9001SK, plastic, plastic guard flush, red, 30mm, spring return, 110-120V

9001SK1L1R

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001SK |
| **Product or Component Type** | Head for illuminated push-button |
| **Device short name** | 9001SK |

## Complementary

| | |
|---|---|
| **Bezel material** | Plastic |
| **Mounting diameter** | 1.2 in (30 mm) |
| **Shape of signaling unit head** | Octagonal |
| **Operator additional information** | Plastic guard |
| **Bulb base** | BA 9s |
| **Light block supply** | Via transformer 120 V AC 50/60 Hz<br>Via transformer 110 V AC 50/60 Hz |
| **Contacts type and composition** | Without contact block |
| **Product Certifications** | UL listed file E42259 CCN NKCR<br>CSA LR24590 class 3211 03<br>CE |
| **NEMA degree of protection** | NEMA 3R/4X/13 |
| **Cap/operator or lens colour** | Red |
| **[Us] rated supply voltage** | 110...120 V |
| **Light block supply** | Via integral transformer |
| **Operator profile** | Flush |
| **Type of operator** | Spring return |
| **Supply frequency** | 50...60 Hz |
| **Size** | 30 mm |
| **Light source** | Incandescent bulb |

## Environment

| | |
|---|---|
| **IP Degree of Protection** | IP65/IP66 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS121429 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901820949 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Returnability** | No |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 5.080 in (12.903 cm) |
| **Package 1 Width** | 2.00 in (5.08 cm) |
| **Package 1 Length** | 12.903 in (32.774 cm) |
| **Package weight(Lbs)** | 6.400 oz (181.437 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Compliant |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |
| WEEE Label | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |