# Product data sheet

Specifications



## Selector switch head, Harmony 9001K, metal, without handle, 30mm, 3 positions, return both sides to center

9001KS57

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Main

| | |
|---|---|
| **Range of Product** | Harmony 9001K |
| **Product or Component Type** | Head for selector switch |
| **Device short name** | 9001KS |
| **Type of operator** | Both sides to centre spring return |

## Complementary

| | |
|---|---|
| **Bezel material** | Metal |
| **Mounting diameter** | 1.2 in (30 mm) |
| **Product Weight** | 0.540 lb(US) (0.245 kg) |
| **Shape of signaling unit head** | Round |
| **Operator position information** | 3 positions |
| **Contacts type and composition** | Without contact block |
| **Mechanical durability** | 0.5 Mcycles |
| **Device presentation** | Basic element |
| **Operator profile** | Without handle |
| **Type of operator** | Spring return |
| **Size** | 30 mm |
| **Return** | Both sides to centre |
| **Cam profile** | 7 |

## Environment

| | |
|---|---|
| **Protective treatment** | TC |
| **Ambient Air Temperature for Storage** | -40…158 °F (-40…70 °C) |
| **Ambient Air Temperature for Operation** | -13…158 °F (-25…70 °C) |
| **Overvoltage category** | Class II conforming to IEC 61140 |
| **IP Degree of Protection** | IP65/IP66 |
| **NEMA degree of protection** | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 6 |

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Standards** | JIS C 4520<br>JIS C 852<br>IEC 60947-5-4<br>CSA C22.2 No 14<br>UL 508<br>IEC 60947-5-1<br>IEC 60947-1 |
| **Product Certifications** | NEMA<br>UL 508 |
| **Vibration resistance** | 7 gn (f= 2…500 Hz) conforming to IEC 60068-2-6 |
| **Shock resistance** | 50 gn IEC 60068-2-27 |

## Ordering and shipping details

| | |
|---|---|
| **Category** | US10CS121426 |
| **Discount Schedule** | 0CS1 |
| **GTIN** | 785901322375 |
| **Returnability** | No |
| **Country of origin** | MX |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Nbr. of units in pkg.** | 1 |
| **Package 1 Height** | 7.620 in (19.355 cm) |
| **Package 1 Width** | 3.00 in (7.62 cm) |
| **Package 1 Length** | 19.355 in (49.161 cm) |
| **Package weight(Lbs)** | 8.000 oz (226.796 g) |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 18 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| SCIP Number | Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d |
| EU RoHS Directive | Compliant By Exemption |
| REACh Regulation | Reference contains Substances of Very High Concern above the threshold |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |

## Use Longer

### Lifetime extension

| | |
|---|---|
| Repair | No |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Circularity Profile | End of Life Information |
| Take-back | No |