Product data sheet
Characteristics

780R301
TRANSFORMER CURRENT

Main

Device short name	780R

Complementary

Accuracy class	Class C50
Electrical connection	Screw clamp terminal
Material	Copper winding
Phase	1 phase
Size	Window 6.5 in
Transformer ratio	300/5

Environment

NEMA degree of protection	NEMA 1
Product certifications	CUL Listed UL Listed

Ordering and shipping details

Category	15500-CLASS 4210 CT'S (LC 5101)
Discount Schedule	PA1
GTIN	00785901969990
Package weight(Lbs)	26.30 lb(US) (11.929 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months